
Hetzner Cloud Python

Release 1.35.0

Hetzner Cloud GmbH

Apr 25, 2024

CONTENTS

1	Stable release	1
2	Via conda (Third-Party)	3
3	From sources	5
4	API References	7
4.1	Main Interface	7
4.2	API Clients	9
4.2.1	ActionsClient	9
4.2.2	CertificateClient	11
4.2.3	DatacentersClient	15
4.2.4	FirewallsClient	17
4.2.5	Floating IPsClient	22
4.2.6	ImagesClient	28
4.2.7	ISOsClient	33
4.2.8	LoadBalancerTypesClient	35
4.2.9	LoadBalancerClient	36
4.2.10	LocationsClient	47
4.2.11	NetworksClient	48
4.2.12	PlacementGroupsClient	55
4.2.13	PrimaryIPsClient	57
4.2.14	ServerTypesClient	62
4.2.15	ServersClient	63
4.2.16	SSHKeysClient	78
4.2.17	VolumesClient	81
4.3	Exceptions	86
4.4	Other	86
4.4.1	Helpers	86
4.4.2	Deprecation Info	87
5	Contributing	89
5.1	Types of Contributions	89
5.1.1	Report Bugs	89
5.1.2	Fix Bugs	89
5.1.3	Implement Features	89
5.1.4	Write Documentation	89
5.1.5	Submit Feedback	90
5.2	Get Started!	90
5.3	Pull Request Guidelines	90

6	Changelog	91
6.1	1.35.0 (2024-04-02)	91
	6.1.1 Features	91
	6.1.2 Bug Fixes	91
6.2	1.34.0 (2024-03-27)	91
	6.2.1 Features	91
6.3	1.33.3 (2024-03-27)	91
	6.3.1 Bug Fixes	91
	6.3.2 Dependencies	91
6.4	1.33.2 (2024-01-02)	92
	6.4.1 Bug Fixes	92
6.5	1.33.1 (2024-01-02)	92
	6.5.1 Bug Fixes	92
	6.5.2 Dependencies	92
6.6	1.33.0 (2023-12-19)	92
	6.6.1 Features	92
	6.6.2 Bug Fixes	93
	6.6.3 Dependencies	93
6.7	1.32.0 (2023-11-17)	93
	6.7.1 Features	93
	6.7.2 Dependencies	93
6.8	1.31.0 (2023-10-23)	93
	6.8.1 Features	93
	6.8.2 Dependencies	93
6.9	1.30.0 (2023-10-13)	94
	6.9.1 Features	94
	6.9.2 Dependencies	94
6.10	1.29.1 (2023-09-26)	94
	6.10.1 Bug Fixes	94
6.11	1.29.0 (2023-09-25)	94
	6.11.1 Features	94
	6.11.2 Bug Fixes	94
	6.11.3 Dependencies	94
	6.11.4 Documentation	95
6.12	1.28.0 (2023-08-17)	95
	6.12.1 Features	95
	6.12.2 Dependencies	95
	6.12.3 Documentation	95
6.13	1.27.2 (2023-08-09)	95
	6.13.1 Documentation	95
6.14	1.27.1 (2023-08-08)	95
	6.14.1 Bug Fixes	95
6.15	1.27.0 (2023-08-08)	96
	6.15.1 Features	96
	6.15.2 Bug Fixes	96
	6.15.3 Dependencies	96
	6.15.4 Documentation	96
6.16	1.26.0 (2023-07-19)	96
	6.16.1 Features	96
6.17	1.25.0 (2023-07-14)	96
	6.17.1 Features	96
	6.17.2 Dependencies	97
6.18	1.24.0 (2023-07-03)	97
	6.18.1 Features	97

6.18.2	Dependencies	97
6.19	1.23.1 (2023-06-30)	97
6.19.1	Bug Fixes	97
6.20	1.23.0 (2023-06-26)	97
6.20.1	Features	97
6.20.2	Bug Fixes	97
6.20.3	Dependencies	97
6.21	1.22.0 (2023-06-22)	98
6.21.1	Features	98
6.21.2	Dependencies	98
6.22	1.21.0 (2023-06-19)	98
6.22.1	Features	98
6.22.2	Bug Fixes	98
6.22.3	Documentation	98
6.23	1.20.0 (2023-05-12)	98
6.23.1	Features	98
6.24	v1.19.0 (2023-04-12)	99
6.25	v1.18.2 (2022-12-27)	99
6.26	v1.18.0 (2022-08-17)	99
6.27	v1.17.0 (2022-06-29)	99
6.28	v1.16.0 (2021-08-17)	99
6.29	v1.15.0 (2021-08-16)	99
6.30	v1.14.1 (2021-08-10)	100
6.31	v1.14.0 (2021-08-03)	100
6.32	v1.13.0 (2021-07-16)	100
6.33	v1.12.0 (2021-04-06)	100
6.34	v1.11.0 (2021-03-11)	100
6.35	v1.10.0 (2020-11-03)	100
6.36	v1.9.1 (2020-08-11)	101
6.37	v1.9.0 (2020-08-10)	101
6.38	v1.8.2 (2020-07-20)	101
6.39	v1.8.1 (2020-06-29)	101
6.40	1.8.0 (2020-06-22)	101
6.41	1.7.1 (2020-06-15)	101
6.42	1.7.0 (2020-06-05)	101
6.43	1.6.3 (2020-01-09)	102
6.44	1.6.2 (2019-10-15)	102
6.45	1.6.1 (2019-10-01)	102
6.46	1.6.0 (2019-09-17)	102
6.47	1.5.0 (2019-09-16)	102
6.48	1.4.1 (2019-08-19)	102
6.49	1.4.0 (2019-07-29)	102
6.50	1.3.0 (2019-07-10)	103
6.51	1.2.1 (2019-03-13)	103
6.52	1.2.0 (2019-03-06)	103
6.53	1.1.0 (2019-02-27)	103
6.54	1.0.1 (2019-02-22)	103
6.55	1.0.0 (2019-02-21)	103
6.56	0.1.0 (2018-12-20)	103
7	Hetzner Cloud Python	105
7.1	Usage	105
7.2	Supported Python versions	106
7.3	Development	106

	7.3.1	Deprecations implementation	106
7.4		License	107
Index			109

STABLE RELEASE

To install Hetzner Cloud Python, run this command in your terminal:

```
$ pip install hcloud
```

This is the preferred method to install Hetzner Cloud Python, as it will always install the most recent stable release. If you don't have [pip](#) installed, this [Python installation guide](#) can guide you through the process.

VIA CONDA (THIRD-PARTY)

Hetzner Cloud Python is also available as a conda-package via *conda-forge*. This package is not maintained by Hetzner Cloud and might be outdated._:

```
$ conda install -c conda-forge hcloud
```


FROM SOURCES

The sources for Hetzner Cloud Python can be downloaded from the Github repo.

You can either clone the public repository:

```
$ git clone git://github.com/hetznercloud/hcloud-python
```

Or download the tarball:

```
$ curl -OL https://github.com/hetznercloud/hcloud-python/tarball/main
```

Once you have a copy of the source, you can install it with:

```
$ pip install .
```


API REFERENCES

4.1 Main Interface

```
class Client(token: str, api_endpoint: str = 'https://api.hetzner.cloud/v1', application_name: str | None = None,
             application_version: str | None = None, poll_interval: int = 1, timeout: float | tuple[float, float] |
             None = None)
```

Base Client for accessing the Hetzner Cloud API

actions

ActionsClient Instance

Type

ActionsClient

certificates

CertificatesClient Instance

Type

CertificatesClient

datacenters

DatacentersClient Instance

Type

DatacentersClient

firewalls

FirewallsClient Instance

Type

FirewallsClient

floating_ips

FloatingIPsClient Instance

Type

FloatingIPsClient

images

ImagesClient Instance

Type

ImagesClient

isos

ImagesClient Instance

Type

IsosClient

load_balancer_types

LoadBalancerTypesClient Instance

Type

LoadBalancerTypesClient

load_balancers

LoadBalancersClient Instance

Type

LoadBalancersClient

locations

LocationsClient Instance

Type

LocationsClient

networks

NetworksClient Instance

Type

NetworksClient

placement_groups

PlacementGroupsClient Instance

Type

PlacementGroupsClient

primary_ips

PrimaryIPsClient Instance

Type

PrimaryIPsClient

request(*method: str, url: str, tries: int = 1, **kwargs*) → dict

Perform a request to the Hetzner Cloud API, wrapper around requests.request

Parameters

- **method** – HTTP Method to perform the Request
- **url** – URL of the Endpoint
- **tries** – Tries of the request (used internally, should not be set by the user)
- **timeout** – Requests timeout in seconds

Returns

Response

server_types

ServerTypesClient Instance

Type

ServerTypesClient

servers

ServersClient Instance

Type*ServersClient***ssh_keys**

SSHKeysClient Instance

Type*SSHKeysClient***volumes**

VolumesClient Instance

Type*VolumesClient*

4.2 API Clients

4.2.1 ActionsClient

class ResourceActionsClient(*client*: *Client*, *resource*: *str* | *None*)**get_all**(*status*: *list[str]* | *None* = *None*, *sort*: *list[str]* | *None* = *None*) → *list[BoundAction]*

Get all actions.

Parameters

- **status** – *List[str]* (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – *List[str]* (optional) Specify how the results are sorted. Choices: *id command status progress started finished* . You can add one of “:asc”, “:desc” to modify sort order. (“:asc” is default)

Returns*List[BoundAction]***get_by_id**(*id*: *int*) → *BoundAction*

Get a specific action by its ID.

Parameters**id** – *int***Returns***BoundAction***get_list**(*status*: *list[str]* | *None* = *None*, *sort*: *list[str]* | *None* = *None*, *page*: *int* | *None* = *None*, *per_page*: *int* | *None* = *None*) → *ActionsPageResult*

Get a list of actions.

Parameters

- **status** – *List[str]* (optional) Response will have only actions with specified statuses. Choices: *running success error*

- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id command status progress started finished* . You can add one of “:asc”, “:desc” to modify sort order. (“:asc” is default)
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[[BoundAction](#)], Meta)

class ActionsClient(client: [Client](#))

get_all(status: list[str] | None = None, sort: list[str] | None = None) → list[[BoundAction](#)]

Deprecated since version 1.28: Use `client.<resource>.actions.get_all()` instead, e.g. using `hcloud.certificates.client.CertificatesClient.actions`.

Starting 1 October 2023, it will no longer be available.

get_by_id(id: int) → [BoundAction](#)

Get a specific action by its ID.

Parameters

id – int

Returns

[BoundAction](#)

get_list(status: list[str] | None = None, sort: list[str] | None = None, page: int | None = None, per_page: int | None = None) → ActionsPageResult

Deprecated since version 1.28: Use `client.<resource>.actions.get_list()` instead, e.g. using `hcloud.certificates.client.CertificatesClient.actions`.

Starting 1 October 2023, it will no longer be available.

class BoundAction(client: ClientEntityBase, data: dict, complete: bool = True)

model

alias of [Action](#)

wait_until_finished(max_retries: int = 100) → None

Wait until the specific action has status=”finished” (set Client.poll_interval to specify a delay between checks)

Parameters

max_retries – int Specify how many retries will be performed before an ActionTimeoutException will be raised

Raises

ActionFailedException when action is finished with status==”error”

Raises

ActionTimeoutException when Action is still in “running” state after max_retries reloads.

class Action(id: int, command: str | None = None, status: str | None = None, progress: int | None = None, started: str | None = None, finished: str | None = None, resources: list[dict] | None = None, error: dict | None = None)

Action Domain

Parameters

- **id** – int ID of an action

- **command** – Command executed in the action
- **status** – Status of the action
- **progress** – Progress of action in percent
- **started** – Point in time when the action was started
- **finished** (*datetime, None*) – Point in time when the action was finished. Only set if the action is finished otherwise None
- **resources** – Resources the action relates to
- **error** – Error message for the action if error occurred, otherwise None.

STATUS_ERROR = 'error'

Action Status error

STATUS_RUNNING = 'running'

Action Status running

STATUS_SUCCESS = 'success'

Action Status success

4.2.2 CertificateClient

class `CertificatesClient`(*client*: `Client`)

actions: `ResourceActionsClient`

Certificates scoped actions client

Type

`ResourceActionsClient`

create(*name*: *str*, *certificate*: *str*, *private_key*: *str*, *labels*: *dict[str, str] | None = None*) → *BoundCertificate*

Creates a new Certificate with the given name, certificate and private_key. This methods allows only creating

custom uploaded certificates. If you want to create a managed certificate use `create_managed()`

Parameters

- **name** – *str*
- **certificate** – *str* Certificate and chain in PEM format, in order so that each record directly certifies the one preceding
- **private_key** – *str* Certificate key in PEM format
- **labels** – *Dict[str, str]* (optional) User-defined labels (key-value pairs)

Returns

BoundCertificate

create_managed(*name*: *str*, *domain_names*: *list[str]*, *labels*: *dict[str, str] | None = None*) →

CreateManagedCertificateResponse

Creates a new managed Certificate with the given name and domain names. This methods allows only creating

managed certificates for domains that are using the Hetzner DNS service. If you want to create a custom uploaded certificate use `create()`

Parameters

- **name** – str
- **domain_names** – List[str] Domains and subdomains that should be contained in the Certificate
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)

Returns

[BoundCertificate](#)

delete(certificate: [Certificate](#) | [BoundCertificate](#)) → bool

Deletes a certificate.

Parameters

certificate – [BoundCertificate](#) or [Certificate](#)

Returns

True

get_actions(certificate: [Certificate](#) | [BoundCertificate](#), status: list[str] | None = None, sort: list[str] | None = None) → list[[BoundAction](#)]

Returns all action objects for a Certificate.

Parameters

- **certificate** – [BoundCertificate](#) or [Certificate](#)
- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

Returns

List[[BoundAction](#)]

get_actions_list(certificate: [Certificate](#) | [BoundCertificate](#), status: list[str] | None = None, sort: list[str] | None = None, page: int | None = None, per_page: int | None = None) → [ActionsPageResult](#)

Returns all action objects for a Certificate.

Parameters

- **certificate** – [BoundCertificate](#) or [Certificate](#)
- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[[BoundAction](#)], Meta)

get_all(*name: str | None = None, label_selector: str | None = None*) → list[*BoundCertificate*]

Get all certificates

Parameters

- **name** – str (optional) Can be used to filter certificates by their name.
- **label_selector** – str (optional) Can be used to filter certificates by labels. The response will only contain certificates matching the label selector.

Returns

List[*BoundCertificate*]

get_by_id(*id: int*) → *BoundCertificate*

Get a specific certificate by its ID.

Parameters

id – int

Returns

BoundCertificate

get_by_name(*name: str*) → *BoundCertificate* | None

Get certificate by name

Parameters

name – str Used to get certificate by name.

Returns

BoundCertificate

get_list(*name: str | None = None, label_selector: str | None = None, page: int | None = None, per_page: int | None = None*) → CertificatesPageResult

Get a list of certificates

Parameters

- **name** – str (optional) Can be used to filter certificates by their name.
- **label_selector** – str (optional) Can be used to filter certificates by labels. The response will only contain certificates matching the label selector.
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[*BoundCertificate*], Meta)

retry_issuance(*certificate: Certificate | BoundCertificate*) → *BoundAction*

Returns all action objects for a Certificate.

Parameters

certificate – *BoundCertificate* or *Certificate*

Returns

BoundAction

update(*certificate: Certificate | BoundCertificate, name: str | None = None, labels: dict[str, str] | None = None*) → *BoundCertificate*

Updates a Certificate. You can update a certificate name and labels.

Parameters

- **certificate** – *BoundCertificate* or *Certificate*
- **name** – str (optional) New name to set
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)

Returns*BoundCertificate***class** *BoundCertificate*(*client*: *CertificatesClient*, *data*: dict, *complete*: bool = True)**delete**() → bool

Deletes a certificate. :return: boolean

get_actions(*status*: list[str] | None = None, *sort*: list[str] | None = None) → list[*BoundAction*]

Returns all action objects for a Certificate.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

ReturnsList[*BoundAction*]**get_actions_list**(*status*: list[str] | None = None, *sort*: list[str] | None = None, *page*: int | None = None, *per_page*: int | None = None) → *ActionsPageResult*

Returns all action objects for a Certificate.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns(List[*BoundAction*], Meta)**model**alias of *Certificate***retry_issuance**() → *BoundAction*Retry a failed Certificate issuance or renewal. :return: *BoundAction***update**(*name*: str | None = None, *labels*: dict[str, str] | None = None) → *BoundCertificate*

Updates an certificate. You can update an certificate name and the certificate labels.

Parameters

- **name** – str (optional) New name to set

- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)

Returns*BoundCertificate*

```
class Certificate(id: int | None = None, name: str | None = None, certificate: str | None = None,
                 not_valid_before: str | None = None, not_valid_after: str | None = None, domain_names:
                 list[str] | None = None, fingerprint: str | None = None, created: str | None = None, labels:
                 dict[str, str] | None = None, type: str | None = None, status: ManagedCertificateStatus | None
                 = None)
```

Certificate Domain

Parameters

- **id** – int ID of Certificate
- **name** – str Name of Certificate
- **certificate** – str Certificate and chain in PEM format, in order so that each record directly certifies the one preceding
- **not_valid_before** – datetime Point in time when the Certificate becomes valid
- **not_valid_after** – datetime Point in time when the Certificate becomes invalid
- **domain_names** – List[str] List of domains and subdomains covered by this certificate
- **fingerprint** – str Fingerprint of the Certificate
- **labels** – dict User-defined labels (key-value pairs)
- **created** – datetime Point in time when the certificate was created
- **type** – str Type of Certificate
- **status** – ManagedCertificateStatus Current status of a type managed Certificate, always none for type uploaded Certificates

4.2.3 DatacentersClient

```
class DatacentersClient(client: Client)
```

```
get_all(name: str | None = None) → list[BoundDatacenter]
```

Get all datacenters

Parameters**name** – str (optional) Can be used to filter datacenters by their name.**Returns**List[*BoundDatacenter*]

```
get_by_id(id: int) → BoundDatacenter
```

Get a specific datacenter by its ID.

Parameters**id** – int**Returns***BoundDatacenter*

get_by_name(name: str) → *BoundDatacenter* | None

Get datacenter by name

Parameters

name – str Used to get datacenter by name.

Returns

BoundDatacenter

get_list(name: str | None = None, page: int | None = None, per_page: int | None = None) →

DatacentersPageResult

Get a list of datacenters

Parameters

- **name** – str (optional) Can be used to filter datacenters by their name.
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[*BoundDatacenter*], *Meta*)

class BoundDatacenter(client: *DatacentersClient*, data: dict)

model

alias of *Datacenter*

class Datacenter(id: int | None = None, name: str | None = None, description: str | None = None, location: *Location* | None = None, server_types: *DatacenterServerTypes* | None = None)

Datacenter Domain

Parameters

- **id** – int ID of Datacenter
- **name** – str Name of Datacenter
- **description** – str Description of Datacenter
- **location** – *BoundLocation*
- **server_types** – *DatacenterServerTypes*

class DatacenterServerTypes(available: list[*BoundServerType*], supported: list[*BoundServerType*], available_for_migration: list[*BoundServerType*])

DatacenterServerTypes Domain

Parameters

- **available** – List[*BoundServerTypes*] All available server types for this datacenter
- **supported** – List[*BoundServerTypes*] All supported server types for this datacenter
- **available_for_migration** – List[*BoundServerTypes*] All available for migration (change type) server types for this datacenter

4.2.4 FirewallsClient

class `FirewallsClient`(*client*: `Client`)

actions: `ResourceActionsClient`

Firewalls scoped actions client

Type

`ResourceActionsClient`

apply_to_resources(*firewall*: `Firewall` | `BoundFirewall`, *resources*: `list[FirewallResource]`) → `list[BoundAction]`

Applies one Firewall to multiple resources.

Parameters

- **firewall** – `BoundFirewall` or `Firewall`
- **resources** – `List[FirewallResource]`

Returns

`List[BoundAction]`

create(*name*: `str`, *rules*: `list[FirewallRule]` | `None` = `None`, *labels*: `str` | `None` = `None`, *resources*: `list[FirewallResource]` | `None` = `None`) → `CreateFirewallResponse`

Creates a new Firewall.

Parameters

- **name** – `str` Firewall Name
- **rules** – `List[FirewallRule]` (optional)
- **labels** – `Dict[str, str]` (optional) User-defined labels (key-value pairs)
- **resources** – `List[FirewallResource]` (optional)

Returns

`CreateFirewallResponse`

delete(*firewall*: `Firewall` | `BoundFirewall`) → `bool`

Deletes a Firewall.

Parameters

firewall – `BoundFirewall` or `Firewall`

Returns

`boolean`

get_actions(*firewall*: `Firewall` | `BoundFirewall`, *status*: `list[str]` | `None` = `None`, *sort*: `list[str]` | `None` = `None`) → `list[BoundAction]`

Returns all action objects for a Firewall.

Parameters

- **firewall** – `BoundFirewall` or `Firewall`
- **status** – `List[str]` (optional) Response will have only actions with specified statuses. Choices: `running success error`
- **sort** – `List[str]` (optional) Specify how the results are sorted. Choices: `id id:asc id:desc command command:asc command:desc status status:asc status:desc progress`

progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc

Returns

List[[BoundAction](#)]

get_actions_list(*firewall: Firewall | BoundFirewall, status: list[str] | None = None, sort: list[str] | None = None, page: int | None = None, per_page: int | None = None*) → ActionsPageResult

Returns all action objects for a Firewall.

Parameters

- **firewall** – [BoundFirewall](#) or [Firewall](#)
- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[[BoundAction](#)], Meta)

get_all(*label_selector: str | None = None, name: str | None = None, sort: list[str] | None = None*) → list[[BoundFirewall](#)]

Get all floating ips from this account

Parameters

- **label_selector** – str (optional) Can be used to filter Firewalls by labels. The response will only contain Firewalls matching the label selector values.
- **name** – str (optional) Can be used to filter networks by their name.
- **sort** – List[str] (optional) Choices: *id name created* (You can add one of “:asc”, “:desc” to modify sort order. (“:asc” is default))

Returns

List[[BoundFirewall](#)]

get_by_id(*id: int*) → [BoundFirewall](#)

Returns a specific Firewall object.

Parameters

id – int

Returns

[BoundFirewall](#)

get_by_name(*name: str*) → [BoundFirewall](#) | None

Get Firewall by name

Parameters

name – str Used to get Firewall by name.

Returns

[BoundFirewall](#)

get_list(*label_selector: str | None = None, page: int | None = None, per_page: int | None = None, name: str | None = None, sort: list[str] | None = None*) → *FirewallsPageResult*

Get a list of floating ips from this account

Parameters

- **label_selector** – str (optional) Can be used to filter Firewalls by labels. The response will only contain Firewalls matching the label selector values.
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page
- **name** – str (optional) Can be used to filter networks by their name.
- **sort** – List[str] (optional) Choices: id name created (You can add one of “:asc”, “:desc” to modify sort order. (“:asc” is default))

Returns

(List[*BoundFirewall*], Meta)

remove_from_resources(*firewall: Firewall | BoundFirewall, resources: list[FirewallResource]*) → list[*BoundAction*]

Removes one Firewall from multiple resources.

Parameters

- **firewall** – *BoundFirewall* or *Firewall*
- **resources** – List[*FirewallResource*]

Returns

List[*BoundAction*]

set_rules(*firewall: Firewall | BoundFirewall, rules: list[FirewallRule]*) → list[*BoundAction*]

Sets the rules of a Firewall. All existing rules will be overwritten. Pass an empty rules array to remove all rules.

Parameters

- **firewall** – *BoundFirewall* or *Firewall*
- **rules** – List[*FirewallRule*]

Returns

List[*BoundAction*]

update(*firewall: Firewall | BoundFirewall, labels: dict[str, str] | None = None, name: str | None = None*) → *BoundFirewall*

Updates the description or labels of a Firewall.

Parameters

- **firewall** – *BoundFirewall* or *Firewall*
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)
- **name** – str (optional) New name to set

Returns

BoundFirewall

class BoundFirewall(*client: FirewallsClient, data: dict, complete: bool = True*)

apply_to_resources(resources: list[[FirewallResource](#)]) → list[[BoundAction](#)]

Applies one Firewall to multiple resources. :param resources: List[[FirewallResource](#)] :return: List[[BoundAction](#)]

delete() → bool

Deletes a Firewall.

Returns

boolean

get_actions(status: list[str] | None = None, sort: list[str] | None = None) → list[[BoundAction](#)]

Returns all action objects for a Firewall.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

Returns

List[[BoundAction](#)]

get_actions_list(status: list[str] | None = None, sort: list[str] | None = None, page: int | None = None, per_page: int | None = None) → ActionsPageResult

Returns all action objects for a Firewall.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[[BoundAction](#)], Meta)

model

alias of [Firewall](#)

remove_from_resources(resources: list[[FirewallResource](#)]) → list[[BoundAction](#)]

Removes one Firewall from multiple resources. :param resources: List[[FirewallResource](#)] :return: List[[BoundAction](#)]

set_rules(rules: list[[FirewallRule](#)]) → list[[BoundAction](#)]

Sets the rules of a Firewall. All existing rules will be overwritten. Pass an empty rules array to remove all rules. :param rules: List[[FirewallRule](#)] :return: List[[BoundAction](#)]

update(name: str | None = None, labels: dict[str, str] | None = None) → [BoundFirewall](#)

Updates the name or labels of a Firewall.

Parameters

- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)
- **name** – str (optional) New Name to set

Returns*BoundFirewall*

```
class Firewall(id: int | None = None, name: str | None = None, labels: dict[str, str] | None = None, rules:
    list[FirewallRule] | None = None, applied_to: list[FirewallResource] | None = None, created: str
    | None = None)
```

Firewall Domain

Parameters

- **id** – int ID of the Firewall
- **name** – str Name of the Firewall
- **labels** – dict User-defined labels (key-value pairs)
- **rules** – List[FirewallRule] Rules of the Firewall
- **applied_to** – List[FirewallResource] Resources currently using the Firewall
- **created** – datetime Point in time when the image was created

```
class FirewallRule(direction: str, protocol: str, source_ips: list[str], port: str | None = None, destination_ips:
    list[str] | None = None, description: str | None = None)
```

Firewall Rule Domain

Parameters

- **direction** – str The Firewall which was created
- **port** – str Port to which traffic will be allowed, only applicable for protocols TCP and UDP, specify port ranges by using - as a indicator, Sample: 80-85 means all ports between 80 & 85 (80, 82, 83, 84, 85)
- **protocol** – str Select traffic direction on which rule should be applied. Use source_ips for direction in and destination_ips for direction out.
- **source_ips** – List[str] List of permitted IPv4/IPv6 addresses in CIDR notation. Use 0.0.0.0/0 to allow all IPv4 addresses and ::/0 to allow all IPv6 addresses. You can specify 100 CIDRs at most.
- **destination_ips** – List[str] List of permitted IPv4/IPv6 addresses in CIDR notation. Use 0.0.0.0/0 to allow all IPv4 addresses and ::/0 to allow all IPv6 addresses. You can specify 100 CIDRs at most.
- **description** – str Short description of the firewall rule

DIRECTION_IN = 'in'

Firewall Rule Direction In

DIRECTION_OUT = 'out'

Firewall Rule Direction Out

PROTOCOL_ESP = 'esp'

Firewall Rule Protocol ESP

PROTOCOL_GRE = 'gre'

Firewall Rule Protocol GRE

PROTOCOL_ICMP = 'icmp'

Firewall Rule Protocol ICMP

PROTOCOL_TCP = 'tcp'

Firewall Rule Protocol TCP

PROTOCOL_UDP = 'udp'

Firewall Rule Protocol UDP

to_payload() → dict[str, Any]

Generates the request payload from this domain object.

class FirewallResource(*type: str, server: Server | BoundServer | None = None, label_selector: FirewallResourceLabelSelector | None = None, applied_to_resources: list[FirewallResourceAppliedToResources] | None = None*)

Firewall Used By Domain

Parameters

- **type** – str Type of resource referenced
- **server** – Optional[Server] Server the Firewall is applied to
- **label_selector** – Optional[FirewallResourceLabelSelector] Label Selector for Servers the Firewall should be applied to
- **applied_to_resources** – (read-only) List of effective resources the firewall is applied to.

TYPE_LABEL_SELECTOR = 'label_selector'

Firewall Used By Type label_selector

TYPE_SERVER = 'server'

Firewall Used By Type Server

to_payload() → dict[str, Any]

Generates the request payload from this domain object.

class CreateFirewallResponse(*firewall: BoundFirewall, actions: list[BoundAction] | None*)

Create Firewall Response Domain

Parameters

- **firewall** – *BoundFirewall* The Firewall which was created
- **actions** – List[*BoundAction*] The Action which shows the progress of the Firewall Creation

4.2.5 Floating IPsClient

class FloatingIPsClient(*client: Client*)

actions: *ResourceActionsClient*

Floating IPs scoped actions client

Type

ResourceActionsClient

assign(floating_ip: FloatingIP | BoundFloatingIP, server: Server | BoundServer) → BoundAction

Assigns a Floating IP to a server.

Parameters

- **floating_ip** – BoundFloatingIP or FloatingIP
- **server** – BoundServer or Server Server the Floating IP shall be assigned to

Returns

BoundAction

change_dns_ptr(floating_ip: FloatingIP | BoundFloatingIP, ip: str, dns_ptr: str) → BoundAction

Changes the hostname that will appear when getting the hostname belonging to this Floating IP.

Parameters

- **floating_ip** – BoundFloatingIP or FloatingIP
- **ip** – str The IP address for which to set the reverse DNS entry
- **dns_ptr** – str Hostname to set as a reverse DNS PTR entry, will reset to original default value if None

Returns

BoundAction

change_protection(floating_ip: FloatingIP | BoundFloatingIP, delete: bool | None = None) →

BoundAction

Changes the protection configuration of the Floating IP.

Parameters

- **floating_ip** – BoundFloatingIP or FloatingIP
- **delete** – boolean If true, prevents the Floating IP from being deleted

Returns

BoundAction

create(type: str, description: str | None = None, labels: str | None = None, home_location: Location | BoundLocation | None = None, server: Server | BoundServer | None = None, name: str | None = None) → CreateFloatingIPResponse

Creates a new Floating IP assigned to a server.

Parameters

- **type** – str Floating IP type Choices: ipv4, ipv6
- **description** – str (optional)
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)
- **home_location** – BoundLocation or Location (Home location (routing is optimized for that location). Only optional if server argument is passed.
- **server** – BoundServer or Server Server to assign the Floating IP to
- **name** – str (optional)

Returns

CreateFloatingIPResponse

delete(floating_ip: FloatingIP | BoundFloatingIP) → bool

Deletes a Floating IP. If it is currently assigned to a server it will automatically get unassigned.

Parameters

floating_ip – BoundFloatingIP or FloatingIP

Returns

boolean

get_actions(floating_ip: FloatingIP | BoundFloatingIP, status: list[str] | None = None, sort: list[str] | None = None) → list[BoundAction]

Returns all action objects for a Floating IP.

Parameters

- **floating_ip** – BoundFloatingIP or FloatingIP
- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

Returns

List[BoundAction]

get_actions_list(floating_ip: FloatingIP | BoundFloatingIP, status: list[str] | None = None, sort: list[str] | None = None, page: int | None = None, per_page: int | None = None) → ActionsPageResult

Returns all action objects for a Floating IP.

Parameters

- **floating_ip** – BoundFloatingIP or FloatingIP
- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[BoundAction], Meta)

get_all(label_selector: str | None = None, name: str | None = None) → list[BoundFloatingIP]

Get all floating ips from this account

Parameters

- **label_selector** – str (optional) Can be used to filter Floating IPs by labels. The response will only contain Floating IPs matching the label selector.able values.
- **name** – str (optional) Can be used to filter networks by their name.

ReturnsList[*BoundFloatingIP*]**get_by_id**(*id*: int) → *BoundFloatingIP*

Returns a specific Floating IP object.

Parameters**id** – int**Returns***BoundFloatingIP***get_by_name**(*name*: str) → *BoundFloatingIP* | None

Get Floating IP by name

Parameters**name** – str Used to get Floating IP by name.**Returns***BoundFloatingIP***get_list**(*label_selector*: str | None = None, *page*: int | None = None, *per_page*: int | None = None, *name*: str | None = None) → FloatingIPsPageResult

Get a list of floating ips from this account

Parameters

- **label_selector** – str (optional) Can be used to filter Floating IPs by labels. The response will only contain Floating IPs matching the label selector.able values.
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page
- **name** – str (optional) Can be used to filter networks by their name.

Returns(List[*BoundFloatingIP*], Meta)**unassign**(*floating_ip*: FloatingIP | *BoundFloatingIP*) → *BoundAction*

Unassigns a Floating IP, resulting in it being unreachable. You may assign it to a server again at a later time.

Parameters**floating_ip** – *BoundFloatingIP* or *FloatingIP***Returns***BoundAction***update**(*floating_ip*: FloatingIP | *BoundFloatingIP*, *description*: str | None = None, *labels*: dict[str, str] | None = None, *name*: str | None = None) → *BoundFloatingIP*

Updates the description or labels of a Floating IP.

Parameters

- **floating_ip** – *BoundFloatingIP* or *FloatingIP*
- **description** – str (optional) New Description to set
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)
- **name** – str (optional) New name to set

Returns*BoundFloatingIP***class** **BoundFloatingIP**(*client: FloatingIPsClient, data: dict, complete: bool = True*)**assign**(*server: Server | BoundServer*) → *BoundAction*

Assigns a Floating IP to a server.

Parameters**server** – *BoundServer* or *Server* Server the Floating IP shall be assigned to**Returns***BoundAction***change_dns_ptr**(*ip: str, dns_ptr: str*) → *BoundAction*

Changes the hostname that will appear when getting the hostname belonging to this Floating IP.

Parameters

- **ip** – str The IP address for which to set the reverse DNS entry
- **dns_ptr** – str Hostname to set as a reverse DNS PTR entry, will reset to original default value if *None*

Returns*BoundAction***change_protection**(*delete: bool | None = None*) → *BoundAction*

Changes the protection configuration of the Floating IP.

Parameters**delete** – boolean If true, prevents the Floating IP from being deleted**Returns***BoundAction***delete**() → bool

Deletes a Floating IP. If it is currently assigned to a server it will automatically get unassigned.

Returns

boolean

get_actions(*status: list[str] | None = None, sort: list[str] | None = None*) → list[*BoundAction*]

Returns all action objects for a Floating IP.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

ReturnsList[*BoundAction*]**get_actions_list**(*status: list[str] | None = None, sort: list[str] | None = None, page: int | None = None, per_page: int | None = None*) → *ActionsPageResult*

Returns all action objects for a Floating IP.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns(List[[BoundAction](#)], Meta)**model**alias of [FloatingIP](#)**unassign()** → [BoundAction](#)

Unassigns a Floating IP, resulting in it being unreachable. You may assign it to a server again at a later time.

Returns[BoundAction](#)**update**(description: str | None = None, labels: dict[str, str] | None = None, name: str | None = None) → [BoundFloatingIP](#)

Updates the description or labels of a Floating IP.

Parameters

- **description** – str (optional) New Description to set
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)
- **name** – str (optional) New Name to set

Returns[BoundFloatingIP](#)

```
class FloatingIP(id: int | None = None, type: str | None = None, description: str | None = None, ip: str | None = None, server: BoundServer | None = None, dns_ptr: list[dict] | None = None, home_location: BoundLocation | None = None, blocked: bool | None = None, protection: dict | None = None, labels: dict[str, str] | None = None, created: str | None = None, name: str | None = None)
```

Floating IP Domain

Parameters

- **id** – int ID of the Floating IP
- **description** – str, None Description of the Floating IP
- **ip** – str IP address of the Floating IP
- **type** – str Type of Floating IP. Choices: *ipv4, ipv6*
- **server** – [BoundServer](#), None Server the Floating IP is assigned to, None if it is not assigned at all
- **dns_ptr** – List[Dict] Array of reverse DNS entries
- **home_location** – [BoundLocation](#) Location the Floating IP was created in. Routing is optimized for this location.

- **blocked** – boolean Whether the IP is blocked
- **protection** – dict Protection configuration for the Floating IP
- **labels** – dict User-defined labels (key-value pairs)
- **created** – datetime Point in time when the Floating IP was created
- **name** – str Name of the Floating IP

class CreateFloatingIPResponse(floating_ip: [BoundFloatingIP](#), action: [BoundAction](#) | None)

Create Floating IP Response Domain

Parameters

- **floating_ip** – [BoundFloatingIP](#) The Floating IP which was created
- **action** – [BoundAction](#) The Action which shows the progress of the Floating IP Creation

4.2.6 ImagesClient

class ImagesClient(client: [Client](#))

actions: [ResourceActionsClient](#)

Images scoped actions client

Type

[ResourceActionsClient](#)

change_protection(image: [Image](#) | [BoundImage](#), delete: bool | None = None) → [BoundAction](#)

Changes the protection configuration of the image. Can only be used on snapshots.

Parameters

- **image** – [BoundImage](#) or [Image](#)
- **delete** – bool If true, prevents the snapshot from being deleted

Returns

[BoundAction](#)

delete(image: [Image](#) | [BoundImage](#)) → bool

Deletes an Image. Only images of type snapshot and backup can be deleted.

:param [BoundImage](#) or [Image](#) :return: bool

get_actions(image: [Image](#) | [BoundImage](#), sort: list[str] | None = None, status: list[str] | None = None) → list[[BoundAction](#)]

Returns all action objects for an image.

Parameters

- **image** – [BoundImage](#) or [Image](#)
- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id command status progress started finished* . You can add one of “:asc”, “:desc” to modify sort order. (“:asc” is default)

Returns

List[[BoundAction](#)]

get_actions_list(image: Image | BoundImage, sort: list[str] | None = None, page: int | None = None, per_page: int | None = None, status: list[str] | None = None) → ActionsPageResult

Returns a list of action objects for an image.

Parameters

- **image** – BoundImage or Image
- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[BoundAction], Meta)

get_all(name: str | None = None, label_selector: str | None = None, bound_to: list[str] | None = None, type: list[str] | None = None, architecture: list[str] | None = None, sort: list[str] | None = None, status: list[str] | None = None, include_deprecated: bool | None = None) → list[BoundImage]

Get all images

Parameters

- **name** – str (optional) Can be used to filter images by their name.
- **label_selector** – str (optional) Can be used to filter servers by labels. The response will only contain servers matching the label selector.
- **bound_to** – List[str] (optional) Server Id linked to the image. Only available for images of type backup
- **type** – List[str] (optional) Choices: *system snapshot backup*
- **architecture** – List[str] (optional) Choices: *x86 arm*
- **status** – List[str] (optional) Can be used to filter images by their status. The response will only contain images matching the status.
- **sort** – List[str] (optional) Choices: *id name created* (You can add one of “:asc”, “:desc” to modify sort order. (“:asc” is default))
- **include_deprecated** – bool (optional) Include deprecated images in the response. Default: False

Returns

List[BoundImage]

get_by_id(id: int) → BoundImage

Get a specific Image

Parameters

id – int

Returns

BoundImage <hcloud.images.client.BoundImage

get_by_name(name: str) → *BoundImage* | None

Get image by name

Parameters

name – str Used to get image by name.

Returns

BoundImage

Deprecated since version 1.19: Use *hcloud.images.client.ImagesClient.get_by_name_and_architecture()* instead.

get_by_name_and_architecture(name: str, architecture: str, *, include_deprecated: bool | None = None) → *BoundImage* | None

Get image by name

Parameters

- **name** – str Used to identify the image.
- **architecture** – str Used to identify the image.
- **include_deprecated** – bool (optional) Include deprecated images. Default: False

Returns

BoundImage

get_list(name: str | None = None, label_selector: str | None = None, bound_to: list[str] | None = None, type: list[str] | None = None, architecture: list[str] | None = None, sort: list[str] | None = None, page: int | None = None, per_page: int | None = None, status: list[str] | None = None, include_deprecated: bool | None = None) → *ImagesPageResult*

Get all images

Parameters

- **name** – str (optional) Can be used to filter images by their name.
- **label_selector** – str (optional) Can be used to filter servers by labels. The response will only contain servers matching the label selector.
- **bound_to** – List[str] (optional) Server Id linked to the image. Only available for images of type backup
- **type** – List[str] (optional) Choices: system snapshot backup
- **architecture** – List[str] (optional) Choices: x86 arm
- **status** – List[str] (optional) Can be used to filter images by their status. The response will only contain images matching the status.
- **sort** – List[str] (optional) Choices: id id:asc id:desc name name:asc name:desc created created:asc created:desc
- **include_deprecated** – bool (optional) Include deprecated images in the response. Default: False
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[*BoundImage*], Meta)

update(*image*: [Image](#) | [BoundImage](#), *description*: *str* | *None* = *None*, *type*: *str* | *None* = *None*, *labels*: *dict*[*str*, *str*] | *None* = *None*) → [BoundImage](#)

Updates the Image. You may change the description, convert a Backup image to a Snapshot Image or change the image labels.

Parameters

- **image** – [BoundImage](#) or [Image](#)
- **description** – *str* (optional) New description of Image
- **type** – *str* (optional) Destination image type to convert to Choices: *snapshot*
- **labels** – *Dict*[*str*, *str*] (optional) User-defined labels (key-value pairs)

Returns

[BoundImage](#)

class BoundImage(*client*: [ImagesClient](#), *data*: *dict*)

change_protection(*delete*: *bool* | *None* = *None*) → [BoundAction](#)

Changes the protection configuration of the image. Can only be used on snapshots.

Parameters

- **delete** – *bool* If true, prevents the snapshot from being deleted

Returns

[BoundAction](#)

delete() → *bool*

Deletes an Image. Only images of type snapshot and backup can be deleted.

Returns

bool

get_actions(*sort*: *list*[*str*] | *None* = *None*, *status*: *list*[*str*] | *None* = *None*) → *list*[[BoundAction](#)]

Returns all action objects for the image.

Parameters

- **status** – *List*[*str*] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – *List*[*str*] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

Returns

List[[BoundAction](#)]

get_actions_list(*sort*: *list*[*str*] | *None* = *None*, *page*: *int* | *None* = *None*, *per_page*: *int* | *None* = *None*, *status*: *list*[*str*] | *None* = *None*) → [ActionsPageResult](#)

Returns a list of action objects for the image.

Parameters

- **status** – *List*[*str*] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – *List*[*str*] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress*

progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc

- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[[BoundAction](#)], Meta)

model

alias of [Image](#)

update(*description: str | None = None, type: str | None = None, labels: dict[str, str] | None = None*) → [BoundImage](#)

Updates the Image. You may change the description, convert a Backup image to a Snapshot Image or change the image labels.

Parameters

- **description** – str (optional) New description of Image
- **type** – str (optional) Destination image type to convert to Choices: *snapshot*
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)

Returns

[BoundImage](#)

class Image(*id: int | None = None, name: str | None = None, type: str | None = None, created: str | None = None, description: str | None = None, image_size: int | None = None, disk_size: int | None = None, deprecated: str | None = None, bound_to: [Server](#) | [BoundServer](#) | None = None, os_flavor: str | None = None, os_version: str | None = None, architecture: str | None = None, rapid_deploy: bool | None = None, created_from: [Server](#) | [BoundServer](#) | None = None, protection: dict | None = None, labels: dict[str, str] | None = None, status: str | None = None*)

Image Domain

Parameters

- **id** – int ID of the image
- **type** – str Type of the image Choices: *system, snapshot, backup, app*
- **status** – str Whether the image can be used or if it's still being created Choices: *available, creating*
- **name** – str, None Unique identifier of the image. This value is only set for system images.
- **description** – str Description of the image
- **image_size** – number, None Size of the image file in our storage in GB. For snapshot images this is the value relevant for calculating costs for the image.
- **disk_size** – number Size of the disk contained in the image in GB.
- **created** – datetime Point in time when the image was created
- **created_from** – [BoundServer](#), None Information about the server the image was created from
- **bound_to** – [BoundServer](#), None ID of server the image is bound to. Only set for images of type *backup*.
- **os_flavor** – str Flavor of operating system contained in the image Choices: *ubuntu, centos, debian, fedora, unknown*

- **os_version** – str, None Operating system version
- **architecture** – str CPU Architecture that the image is compatible with. Choices: *x86*, *arm*
- **rapid_deploy** – bool Indicates that rapid deploy of the image is available
- **protection** – dict Protection configuration for the image
- **deprecated** – datetime, None Point in time when the image is considered to be deprecated (in ISO-8601 format)
- **labels** – Dict User-defined labels (key-value pairs)

class CreateImageResponse(*action*: [BoundAction](#), *image*: [BoundImage](#))

Create Image Response Domain

Parameters

- **image** – [BoundImage](#) The Image which was created
- **action** – [BoundAction](#) The Action which shows the progress of the Floating IP Creation

4.2.7 ISOsClient

class IsosClient(*client*: [Client](#))

get_all(*name*: str | None = None, *architecture*: list[str] | None = None, *include_wildcard_architecture*: bool | None = None, *include_architecture_wildcard*: bool | None = None) → list[[BoundIso](#)]

Get all ISOs

Parameters

- **name** – str (optional) Can be used to filter ISOs by their name.
- **architecture** – List[str] (optional) Can be used to filter ISOs by their architecture. Choices: *x86* *arm*
- **include_wildcard_architecture** – bool (optional) Deprecated, please use *include_architecture_wildcard* instead.
- **include_architecture_wildcard** – bool (optional) Custom ISOs do not have an architecture set. You must also set this flag to True if you are filtering by architecture and also want custom ISOs.

Returns

List[[BoundIso](#)]

get_by_id(*id*: int) → [BoundIso](#)

Get a specific ISO by its id

Parameters

id – int

Returns

[BoundIso](#)

get_by_name(*name*: str) → [BoundIso](#) | None

Get iso by name

Parameters

name – str Used to get iso by name.

Returns*BoundIso*

get_list(*name: str | None = None, architecture: list[str] | None = None, include_wildcard_architecture: bool | None = None, include_architecture_wildcard: bool | None = None, page: int | None = None, per_page: int | None = None*) → *IsosPageResult*

Get a list of ISOs

Parameters

- **name** – str (optional) Can be used to filter ISOs by their name.
- **architecture** – List[str] (optional) Can be used to filter ISOs by their architecture. Choices: *x86 arm*
- **include_wildcard_architecture** – bool (optional) Deprecated, please use *include_architecture_wildcard* instead.
- **include_architecture_wildcard** – bool (optional) Custom ISOs do not have an architecture set. You must also set this flag to True if you are filtering by architecture and also want custom ISOs.
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[*BoundIso*], *Meta*)

class BoundIso(*client: ClientEntityBase, data: dict, complete: bool = True*)

model

alias of *Iso*

class Iso(*id: int | None = None, name: str | None = None, type: str | None = None, architecture: str | None = None, description: str | None = None, deprecated: str | None = None, deprecation: dict | None = None*)

Iso Domain

Parameters

- **id** – int ID of the ISO
- **name** – str, None Unique identifier of the ISO. Only set for public ISOs
- **description** – str Description of the ISO
- **type** – str Type of the ISO. Choices: *public, private*
- **architecture** – str, None CPU Architecture that the ISO is compatible with. None means that the compatibility is unknown. Choices: *x86, arm*
- **deprecated** – datetime, None ISO 8601 timestamp of deprecation, None if ISO is still available. After the deprecation time it will no longer be possible to attach the ISO to servers. This field is deprecated. Use *deprecation* instead.
- **deprecation** – *DeprecationInfo*, None Describes if, when & how the resources was deprecated. If this field is set to None the resource is not deprecated. If it has a value, it is considered deprecated.

property deprecated: *datetime | None*

ISO 8601 timestamp of deprecation, None if ISO is still available.

4.2.8 LoadBalancerTypesClient

class `LoadBalancerTypesClient`(*client*: `Client`)

get_all(*name*: `str` | `None` = `None`) → `list`[`BoundLoadBalancerType`]

Get all Load Balancer types

Parameters

name – `str` (optional) Can be used to filter Load Balancer type by their name.

Returns

`List`[`BoundLoadBalancerType`]

get_by_id(*id*: `int`) → `BoundLoadBalancerType`

Returns a specific Load Balancer Type.

Parameters

id – `int`

Returns

`BoundLoadBalancerType`

get_by_name(*name*: `str`) → `BoundLoadBalancerType` | `None`

Get Load Balancer type by name

Parameters

name – `str` Used to get Load Balancer type by name.

Returns

`BoundLoadBalancerType`

get_list(*name*: `str` | `None` = `None`, *page*: `int` | `None` = `None`, *per_page*: `int` | `None` = `None`) → `LoadBalancerTypesPageResult`

Get a list of Load Balancer types

Parameters

- **name** – `str` (optional) Can be used to filter Load Balancer type by their name.
- **page** – `int` (optional) Specifies the page to fetch
- **per_page** – `int` (optional) Specifies how many results are returned by page

Returns

(`List`[`BoundLoadBalancerType`], `Meta`)

class `LoadBalancerType`(*id*: `int` | `None` = `None`, *name*: `str` | `None` = `None`, *description*: `str` | `None` = `None`, *max_connections*: `int` | `None` = `None`, *max_services*: `int` | `None` = `None`, *max_targets*: `int` | `None` = `None`, *max_assigned_certificates*: `int` | `None` = `None`, *prices*: `dict` | `None` = `None`)

`LoadBalancerType` Domain

Parameters

- **id** – `int` ID of the Load Balancer type
- **name** – `str` Name of the Load Balancer type
- **description** – `str` Description of the Load Balancer type
- **max_connections** – `int` Max amount of connections the Load Balancer can handle
- **max_services** – `int` Max amount of services the Load Balancer can handle

- **max_targets** – int Max amount of targets the Load Balancer can handle
- **max_assigned_certificates** – int Max amount of certificates the Load Balancer can serve
- **prices** – Dict Prices in different locations

4.2.9 LoadBalancerClient

class LoadBalancersClient(*client*: Client)

actions: *ResourceActionsClient*

Load Balancers scoped actions client

Type

ResourceActionsClient

add_service(*load_balancer*: LoadBalancer | BoundLoadBalancer, *service*: LoadBalancerService) → *BoundAction*

Adds a service to a Load Balancer.

Parameters

- **load_balancer** – *BoundLoadBalancer* or *LoadBalancer*
- **service** – *LoadBalancerService* The LoadBalancerService you want to add to the Load Balancer

Returns

BoundAction

add_target(*load_balancer*: LoadBalancer | BoundLoadBalancer, *target*: LoadBalancerTarget) → *BoundAction*

Adds a target to a Load Balancer.

Parameters

- **load_balancer** – *BoundLoadBalancer* or *LoadBalancer*
- **target** – *LoadBalancerTarget* The LoadBalancerTarget you want to add to the Load Balancer

Returns

BoundAction

attach_to_network(*load_balancer*: LoadBalancer | BoundLoadBalancer, *network*: Network | BoundNetwork, *ip*: str | None = None) → *BoundAction*

Attach a Load Balancer to a Network.

Parameters

- **load_balancer** – :class:`<hcloud.load_balancers.client.BoundLoadBalancer>` or *LoadBalancer*
- **network** – *BoundNetwork* or *Network*
- **ip** – str IP to request to be assigned to this Load Balancer

Returns

BoundAction

change_algorithm(load_balancer: LoadBalancer | BoundLoadBalancer, algorithm: LoadBalancerAlgorithm) → BoundAction

Changes the algorithm used by the Load Balancer

Parameters

- **load_balancer** – :class:` <hcloud.load_balancers.client.BoundLoadBalancer>` or *LoadBalancer*
- **algorithm** – *LoadBalancerAlgorithm* The LoadBalancerSubnet you want to add to the Load Balancer

Returns

BoundAction

change_dns_ptr(load_balancer: LoadBalancer | BoundLoadBalancer, ip: str, dns_ptr: str) → BoundAction

Changes the hostname that will appear when getting the hostname belonging to the public IPs (IPv4 and IPv6) of this Load Balancer.

Parameters

- **ip** – str The IP address for which to set the reverse DNS entry
- **dns_ptr** – str Hostname to set as a reverse DNS PTR entry, will reset to original default value if *None*

Returns

BoundAction

change_protection(load_balancer: LoadBalancer | BoundLoadBalancer, delete: bool | None = None) → BoundAction

Changes the protection configuration of a Load Balancer.

Parameters

- **load_balancer** – :class:` <hcloud.load_balancers.client.BoundLoadBalancer>` or *LoadBalancer*
- **delete** – boolean If True, prevents the Load Balancer from being deleted

Returns

BoundAction

change_type(load_balancer: LoadBalancer | BoundLoadBalancer, load_balancer_type: LoadBalancerType | BoundLoadBalancerType) → BoundAction

Changes the type of a Load Balancer.

Parameters

- **load_balancer** – *BoundLoadBalancer* or *LoadBalancer*
- **load_balancer_type** – *BoundLoadBalancerType* or *LoadBalancerType* Load Balancer type the Load Balancer should migrate to

Returns

BoundAction

create(name: str, load_balancer_type: LoadBalancerType | BoundLoadBalancerType, algorithm: LoadBalancerAlgorithm | None = None, services: list[LoadBalancerService] | None = None, targets: list[LoadBalancerTarget] | None = None, labels: dict[str, str] | None = None, location: Location | BoundLocation | None = None, network_zone: str | None = None, public_interface: bool | None = None, network: Network | BoundNetwork | None = None) → CreateLoadBalancerResponse

Creates a Load Balancer .

Parameters

- **name** – str Name of the Load Balancer
- **load_balancer_type** – LoadBalancerType Type of the Load Balancer
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)
- **location** – Location Location of the Load Balancer
- **network_zone** – str Network Zone of the Load Balancer
- **algorithm** – LoadBalancerAlgorithm (optional) The algorithm the Load Balancer is currently using
- **services** – LoadBalancerService The services the Load Balancer is currently serving
- **targets** – LoadBalancerTarget The targets the Load Balancer is currently serving
- **public_interface** – bool Enable or disable the public interface of the Load Balancer
- **network** – Network Adds the Load Balancer to a Network

Returns

CreateLoadBalancerResponse

delete(load_balancer: LoadBalancer | BoundLoadBalancer) → bool

Deletes a Load Balancer.

Parameters

load_balancer – BoundLoadBalancer or LoadBalancer

Returns

boolean

delete_service(load_balancer: LoadBalancer | BoundLoadBalancer, service: LoadBalancerService) → BoundAction

Deletes a service from a Load Balancer.

Parameters

- **load_balancer** – BoundLoadBalancer or LoadBalancer
- **service** – LoadBalancerService The LoadBalancerService you want to delete from the Load Balancer

Returns

BoundAction

detach_from_network(load_balancer: LoadBalancer | BoundLoadBalancer, network: Network | BoundNetwork) → BoundAction

Detaches a Load Balancer from a Network.

Parameters

- **load_balancer** – :class:`<hcloud.load_balancers.client.BoundLoadBalancer>` or LoadBalancer
- **network** – BoundNetwork or Network

Returns

BoundAction

disable_public_interface(load_balancer: [LoadBalancer](#) | [BoundLoadBalancer](#)) → [BoundAction](#)

Disables the public interface of a Load Balancer.

Parameters

load_balancer – :class:` <hcloud.load_balancers.client.BoundLoadBalancer>` or [LoadBalancer](#)

Returns

[BoundAction](#)

enable_public_interface(load_balancer: [LoadBalancer](#) | [BoundLoadBalancer](#)) → [BoundAction](#)

Enables the public interface of a Load Balancer.

Parameters

load_balancer – :class:` <hcloud.load_balancers.client.BoundLoadBalancer>` or [LoadBalancer](#)

Returns

[BoundAction](#)

get_actions(load_balancer: [LoadBalancer](#) | [BoundLoadBalancer](#), status: list[str] | None = None, sort: list[str] | None = None) → list[[BoundAction](#)]

Returns all action objects for a Load Balancer.

Parameters

- **load_balancer** – [BoundLoadBalancer](#) or [LoadBalancer](#)
- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

Returns

List[[BoundAction](#)]

get_actions_list(load_balancer: [LoadBalancer](#) | [BoundLoadBalancer](#), status: list[str] | None = None, sort: list[str] | None = None, page: int | None = None, per_page: int | None = None) → [ActionsPageResult](#)

Returns all action objects for a Load Balancer.

Parameters

- **load_balancer** – [BoundLoadBalancer](#) or [LoadBalancer](#)
- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[[BoundAction](#)], [Meta](#))

get_all(name: str | None = None, label_selector: str | None = None) → list[[BoundLoadBalancer](#)]

Get all Load Balancers from this account

Parameters

- **name** – str (optional) Can be used to filter Load Balancers by their name.
- **label_selector** – str (optional) Can be used to filter Load Balancers by labels. The response will only contain Load Balancers matching the label selector.

Returns

List[[BoundLoadBalancer](#)]

get_by_id(id: int) → [BoundLoadBalancer](#)

Get a specific Load Balancer

Parameters

id – int

Returns

[BoundLoadBalancer](#)

get_by_name(name: str) → [BoundLoadBalancer](#) | None

Get Load Balancer by name

Parameters

name – str Used to get Load Balancer by name.

Returns

[BoundLoadBalancer](#)

get_list(name: str | None = None, label_selector: str | None = None, page: int | None = None, per_page: int | None = None) → LoadBalancersPageResult

Get a list of Load Balancers from this account

Parameters

- **name** – str (optional) Can be used to filter Load Balancers by their name.
- **label_selector** – str (optional) Can be used to filter Load Balancers by labels. The response will only contain Load Balancers matching the label selector.
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[[BoundLoadBalancer](#)], Meta)

get_metrics(load_balancer: [LoadBalancer](#) | [BoundLoadBalancer](#), type: Literal['open_connections', 'connections_per_second', 'requests_per_second', 'bandwidth'] | list[Literal['open_connections', 'connections_per_second', 'requests_per_second', 'bandwidth']], start: datetime | str, end: datetime | str, step: float | None = None) → GetMetricsResponse

Get Metrics for a LoadBalancer.

Parameters

- **load_balancer** – The Load Balancer to get the metrics for.
- **type** – Type of metrics to get.
- **start** – Start of period to get Metrics for (in ISO-8601 format).

- **end** – End of period to get Metrics for (in ISO-8601 format).
- **step** – Resolution of results in seconds.

remove_target(*load_balancer*: *LoadBalancer* | *BoundLoadBalancer*, *target*: *LoadBalancerTarget*) → *BoundAction*

Removes a target from a Load Balancer.

Parameters

- **load_balancer** – *BoundLoadBalancer* or *LoadBalancer*
- **target** – *LoadBalancerTarget* The *LoadBalancerTarget* you want to remove from the Load Balancer

Returns

BoundAction

update(*load_balancer*: *LoadBalancer* | *BoundLoadBalancer*, *name*: *str* | *None* = *None*, *labels*: *dict[str, str]* | *None* = *None*) → *BoundLoadBalancer*

Updates a LoadBalancer. You can update a LoadBalancer's name and a LoadBalancer's labels.

Parameters

- **load_balancer** – *BoundLoadBalancer* or *LoadBalancer*
- **name** – *str* (optional) New name to set
- **labels** – *Dict[str, str]* (optional) User-defined labels (key-value pairs)

Returns

BoundLoadBalancer

update_service(*load_balancer*: *LoadBalancer* | *BoundLoadBalancer*, *service*: *LoadBalancerService*) → *BoundAction*

Updates a service of an Load Balancer.

Parameters

- **load_balancer** – *BoundLoadBalancer* or *LoadBalancer*
- **service** – *LoadBalancerService* The *LoadBalancerService* with updated values within for the Load Balancer

Returns

BoundAction

class BoundLoadBalancer(*client*: *LoadBalancersClient*, *data*: *dict*, *complete*: *bool* = *True*)

add_service(*service*: *LoadBalancerService*) → *BoundAction*

Adds a service to a Load Balancer.

Parameters

- **service** – *LoadBalancerService* The *LoadBalancerService* you want to add to the Load Balancer

Returns

BoundAction

add_target(*target*: *LoadBalancerTarget*) → *BoundAction*

Adds a target to a Load Balancer.

Parameters

target – *LoadBalancerTarget* The LoadBalancerTarget you want to add to the Load Balancer

Returns

BoundAction

attach_to_network(*network*: *Network* | *BoundNetwork*, *ip*: *str* | *None* = *None*) → *BoundAction*

Attaches a Load Balancer to a Network

Parameters

- **network** – *BoundNetwork* or *Network*
- **ip** – str IP to request to be assigned to this Load Balancer

Returns

BoundAction

change_algorithm(*algorithm*: *LoadBalancerAlgorithm*) → *BoundAction*

Changes the algorithm used by the Load Balancer

Parameters

algorithm – *LoadBalancerAlgorithm* The LoadBalancerAlgorithm you want to use

Returns

BoundAction

change_dns_ptr(*ip*: *str*, *dns_ptr*: *str*) → *BoundAction*

Changes the hostname that will appear when getting the hostname belonging to the public IPs (IPv4 and IPv6) of this Load Balancer.

Parameters

- **ip** – str The IP address for which to set the reverse DNS entry
- **dns_ptr** – str Hostname to set as a reverse DNS PTR entry, will reset to original default value if *None*

Returns

BoundAction

change_protection(*delete*: *bool*) → *BoundAction*

Changes the protection configuration of a Load Balancer.

Parameters

delete – boolean If True, prevents the Load Balancer from being deleted

Returns

BoundAction

change_type(*load_balancer_type*: *LoadBalancerType* | *BoundLoadBalancerType*) → *BoundAction*

Changes the type of a Load Balancer.

Parameters

load_balancer_type – *BoundLoadBalancerType* or *LoadBalancerType* Load Balancer type the Load Balancer should migrate to

Returns

BoundAction

delete() → bool

Deletes a Load Balancer.

Returns

boolean

delete_service(service: [LoadBalancerService](#)) → [BoundAction](#)

Deletes a service from a Load Balancer.

Parameters

service – [LoadBalancerService](#) The LoadBalancerService you want to delete from the Load Balancer

Returns

[BoundAction](#)

detach_from_network(network: [Network](#) | [BoundNetwork](#)) → [BoundAction](#)

Detaches a Load Balancer from a Network.

Parameters

network – [BoundNetwork](#) or [Network](#)

Returns

[BoundAction](#)

disable_public_interface() → [BoundAction](#)

Disables the public interface of a Load Balancer.

Returns

[BoundAction](#)

enable_public_interface() → [BoundAction](#)

Enables the public interface of a Load Balancer.

Returns

[BoundAction](#)

get_actions(status: list[str] | None = None, sort: list[str] | None = None) → list[[BoundAction](#)]

Returns all action objects for a Load Balancer.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

Returns

List[[BoundAction](#)]

get_actions_list(status: list[str] | None = None, sort: list[str] | None = None, page: int | None = None, per_page: int | None = None) → [ActionsPageResult](#)

Returns all action objects for a Load Balancer.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*

- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[[BoundAction](#)], Meta)

get_metrics(*type: Literal['open_connections', 'connections_per_second', 'requests_per_second', 'bandwidth'], start: datetime | str, end: datetime | str, step: float | None = None*) → GetMetricsResponse

Get Metrics for a LoadBalancer.

Parameters

- **type** – Type of metrics to get.
- **start** – Start of period to get Metrics for (in ISO-8601 format).
- **end** – End of period to get Metrics for (in ISO-8601 format).
- **step** – Resolution of results in seconds.

model

alias of [LoadBalancer](#)

remove_target(*target: LoadBalancerTarget*) → [BoundAction](#)

Removes a target from a Load Balancer.

Parameters

target – [LoadBalancerTarget](#) The LoadBalancerTarget you want to remove from the Load Balancer

Returns

[BoundAction](#)

update(*name: str | None = None, labels: dict[str, str] | None = None*) → [BoundLoadBalancer](#)

Updates a Load Balancer. You can update a Load Balancers name and a Load Balancers labels.

Parameters

- **name** – str (optional) New name to set
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)

Returns

[BoundLoadBalancer](#)

update_service(*service: LoadBalancerService*) → [BoundAction](#)

Updates a service of an Load Balancer.

Parameters

service – [LoadBalancerService](#) The LoadBalancerService you want to update

Returns

[BoundAction](#)

```
class LoadBalancer(id: int, name: str | None = None, public_net: PublicNetwork | None = None, private_net:
    list[PrivateNet] | None = None, location: BoundLocation | None = None, algorithm:
    LoadBalancerAlgorithm | None = None, services: list[LoadBalancerService] | None =
    None, load_balancer_type: BoundLoadBalancerType | None = None, protection: dict |
    None = None, labels: dict[str, str] | None = None, targets: list[LoadBalancerTarget] | None
    = None, created: str | None = None, outgoing_traffic: int | None = None, ingoing_traffic:
    int | None = None, included_traffic: int | None = None)
```

LoadBalancer Domain

Parameters

- **id** – int ID of the Load Balancer
- **name** – str Name of the Load Balancer (must be unique per project)
- **created** – datetime Point in time when the Load Balancer was created
- **protection** – dict Protection configuration for the Load Balancer
- **labels** – dict User-defined labels (key-value pairs)
- **location** – Location Location of the Load Balancer
- **public_net** – PublicNetwork Public network information.
- **private_net** – List[PrivateNet <hcloud.load_balancers.domain.PrivateNet] Private networks information.
- **algorithm** – LoadBalancerAlgorithm The algorithm the Load Balancer is currently using
- **services** – List[LoadBalancerService] The services the LoadBalancer is currently serving
- **targets** – LoadBalancerTarget The targets the LoadBalancer is currently serving
- **load_balancer_type** – LoadBalancerType The type of the Load Balancer
- **outgoing_traffic** – int, None Outbound Traffic for the current billing period in bytes
- **ingoing_traffic** – int, None Inbound Traffic for the current billing period in bytes
- **included_traffic** – int Free Traffic for the current billing period in bytes

```
class LoadBalancerService(protocol: str | None = None, listen_port: int | None = None, destination_port: int |
    None = None, proxyprotocol: bool | None = None, health_check:
    LoadBalancerHealthCheck | None = None, http: LoadBalancerServiceHttp | None
    = None)
```

LoadBalancerService Domain

Parameters

- **protocol** – str Protocol of the service Choices: tcp, http, https
- **listen_port** – int Required when protocol is tcp, must be unique per Load Balancer.
- **destination_port** – int Required when protocol is tcp
- **proxyprotocol** – bool Enable proxyprotocol
- **health_check** – LoadBalancerHealthCheck Configuration for health checks
- **http** – LoadBalancerServiceHttp Configuration for http/https protocols, required when protocol is http/https

to_payload() → dict[str, Any]

Generates the request payload from this domain object.

```
class LoadBalancerServiceHttp(cookie_name: str | None = None, cookie_lifetime: str | None = None,
                               certificates: list[BoundCertificate] | None = None, redirect_http: bool | None
                               = None, sticky_sessions: bool | None = None)
```

LoadBalancerServiceHttp Domain

Parameters

- **cookie_name** – str Name of the cookie used for Session Stickness
- **cookie_lifetime** – str Lifetime of the cookie used for Session Stickness
- **certificates** – list IDs of the Certificates to use for TLS/SSL termination by the Load Balancer; empty for TLS/SSL passthrough or if protocol is “http”
- **redirect_http** – bool Redirect traffic from http port 80 to port 443
- **sticky_sessions** – bool Use sticky sessions. Only available if protocol is “http” or “https”.

```
class LoadBalancerHealthCheck(protocol: str | None = None, port: int | None = None, interval: int | None =
                               None, timeout: int | None = None, retries: int | None = None, http:
                               LoadBalancerHealtCheckHttp | None = None)
```

LoadBalancerHealthCheck Domain

Parameters

- **protocol** – str Protocol of the service Choices: tcp, http, https
- **port** – int Port the healthcheck will be performed on
- **interval** – int Interval we trigger health check in
- **timeout** – int Timeout in sec after a try is assumed as timeout
- **retries** – int Retries we perform until we assume a target as unhealthy
- **http** – LoadBalancerHealtCheckHttp HTTP Config

```
class LoadBalancerHealtCheckHttp(domain: str | None = None, path: str | None = None, response: str | None
                                  = None, status_codes: list | None = None, tls: bool | None = None)
```

LoadBalancerHealtCheckHttp Domain

Parameters

- **domain** – str Domain name to send in HTTP request. Can be null: In that case we will not send a domain name
- **path** – str HTTP Path send in Request
- **response** – str Optional HTTP response to receive in order to pass the health check
- **status_codes** – list List of HTTP status codes to receive in order to pass the health check
- **tls** – bool Type of health check

```
class LoadBalancerTarget(type: str | None = None, server: BoundServer | None = None, label_selector:
                          LoadBalancerTargetLabelSelector | None = None, ip: LoadBalancerTargetIP | None
                          = None, use_private_ip: bool | None = None, health_status:
                          list[LoadBalancerTargetHealthStatus] | None = None)
```

LoadBalancerTarget Domain

Parameters

- **type** – str Type of the resource, can be server or label_selector
- **server** – Server Target server

- **label_selector** – LoadBalancerTargetLabelSelector Target label selector
- **ip** – LoadBalancerTargetIP Target IP
- **use_private_ip** – bool use the private IP instead of primary public IP
- **health_status** – list List of health statuses of the services on this target. Only present for target types “server” and “ip”.

to_payload() → dict[str, Any]

Generates the request payload from this domain object.

class LoadBalancerTargetHealthStatus(*listen_port: int | None = None, status: str | None = None*)

LoadBalancerTargetHealthStatus Domain

Parameters

- **listen_port** – Load Balancer Target listen port
- **status** – Load Balancer Target status. Choices: healthy, unhealthy, unknown

class LoadBalancerTargetLabelSelector(*selector: str | None = None*)

LoadBalancerTargetLabelSelector Domain

Parameters

selector – str Target label selector

class LoadBalancerTargetIP(*ip: str | None = None*)

LoadBalancerTargetIP Domain

Parameters

ip – str Target IP

class LoadBalancerAlgorithm(*type: str | None = None*)

LoadBalancerAlgorithm Domain

Parameters

type – str Algorithm of the Load Balancer. Choices: round_robin, least_connections

4.2.10 LocationsClient

class LocationsClient(*client: Client*)

get_all(*name: str | None = None*) → list[*BoundLocation*]

Get all locations

Parameters

name – str (optional) Can be used to filter locations by their name.

Returns

List[*BoundLocation*]

get_by_id(*id: int*) → *BoundLocation*

Get a specific location by its ID.

Parameters

id – int

Returns

BoundLocation

get_by_name(name: str) → *BoundLocation* | None

Get location by name

Parameters

name – str Used to get location by name.

Returns

BoundLocation

get_list(name: str | None = None, page: int | None = None, per_page: int | None = None) →

LocationsPageResult

Get a list of locations

Parameters

- **name** – str (optional) Can be used to filter locations by their name.
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[*BoundLocation*], Meta)

class BoundLocation(client: ClientEntityBase, data: dict, complete: bool = True)

model

alias of *Location*

class Location(id: int | None = None, name: str | None = None, description: str | None = None, country: str | None = None, city: str | None = None, latitude: float | None = None, longitude: float | None = None, network_zone: str | None = None)

Location Domain

Parameters

- **id** – int ID of location
- **name** – str Name of location
- **description** – str Description of location
- **country** – str ISO 3166-1 alpha-2 code of the country the location resides in
- **city** – str City the location is closest to
- **latitude** – float Latitude of the city closest to the location
- **longitude** – float Longitude of the city closest to the location
- **network_zone** – str Name of network zone this location resides in

4.2.11 NetworksClient

class NetworksClient(client: Client)

actions: *ResourceActionsClient*

Networks scoped actions client

Type

ResourceActionsClient

add_route(*network*: [Network](#) | [BoundNetwork](#), *route*: [NetworkRoute](#)) → [BoundAction](#)

Adds a route entry to a network.

Parameters

- **network** – [BoundNetwork](#) or [Network](#)
- **route** – [NetworkRoute](#) The NetworkRoute you want to add to the Network

Returns

[BoundAction](#)

add_subnet(*network*: [Network](#) | [BoundNetwork](#), *subnet*: [NetworkSubnet](#)) → [BoundAction](#)

Adds a subnet entry to a network.

Parameters

- **network** – [BoundNetwork](#) or [Network](#)
- **subnet** – [NetworkSubnet](#) The NetworkSubnet you want to add to the Network

Returns

[BoundAction](#)

change_ip_range(*network*: [Network](#) | [BoundNetwork](#), *ip_range*: *str*) → [BoundAction](#)

Changes the IP range of a network.

Parameters

- **network** – [BoundNetwork](#) or [Network](#)
- **ip_range** – *str* The new prefix for the whole network.

Returns

[BoundAction](#)

change_protection(*network*: [Network](#) | [BoundNetwork](#), *delete*: *bool* | *None* = *None*) → [BoundAction](#)

Changes the protection configuration of a network.

Parameters

- **network** – [BoundNetwork](#) or [Network](#)
- **delete** – *boolean* If True, prevents the network from being deleted

Returns

[BoundAction](#)

create(*name*: *str*, *ip_range*: *str*, *subnets*: *list*[[NetworkSubnet](#)] | *None* = *None*, *routes*: *list*[[NetworkRoute](#)] | *None* = *None*, *expose_routes_to_vswitch*: *bool* | *None* = *None*, *labels*: *dict*[*str*, *str*] | *None* = *None*) → [BoundNetwork](#)

Creates a network with range *ip_range*.

Parameters

- **name** – *str* Name of the network
- **ip_range** – *str* IP range of the whole network which must span all included subnets and route destinations
- **subnets** – *List*[[NetworkSubnet](#)] Array of subnets allocated
- **routes** – *List*[[NetworkRoute](#)] Array of routes set in this network

- **expose_routes_to_vswitch** – Optional[bool] Indicates if the routes from this network should be exposed to the vSwitch connection. The exposing only takes effect if a vSwitch connection is active.
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)

Returns*BoundNetwork***delete**(*network*: *Network* | *BoundNetwork*) → bool

Deletes a network.

Parameters**network** – *BoundNetwork* or *Network***Returns**

boolean

delete_route(*network*: *Network* | *BoundNetwork*, *route*: *NetworkRoute*) → *BoundAction*

Removes a route entry to a network.

Parameters

- **network** – *BoundNetwork* or *Network*
- **route** – *NetworkRoute* The NetworkRoute you want to remove from the Network

Returns*BoundAction***delete_subnet**(*network*: *Network* | *BoundNetwork*, *subnet*: *NetworkSubnet*) → *BoundAction*

Removes a subnet entry from a network

Parameters

- **network** – *BoundNetwork* or *Network*
- **subnet** – *NetworkSubnet* The NetworkSubnet you want to remove from the Network

Returns*BoundAction***get_actions**(*network*: *Network* | *BoundNetwork*, *status*: list[str] | None = None, *sort*: list[str] | None = None) → list[*BoundAction*]

Returns all action objects for a network.

Parameters

- **network** – *BoundNetwork* or *Network*
- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

ReturnsList[*BoundAction*]**get_actions_list**(*network*: *Network* | *BoundNetwork*, *status*: list[str] | None = None, *sort*: list[str] | None = None, *page*: int | None = None, *per_page*: int | None = None) → *ActionsPageResult*

Returns all action objects for a network.

Parameters

- **network** – *BoundNetwork* or *Network*
- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns(List[*BoundAction*], Meta)**get_all**(name: str | None = None, label_selector: str | None = None) → list[*BoundNetwork*]

Get all networks from this account

Parameters

- **name** – str (optional) Can be used to filter networks by their name.
- **label_selector** – str (optional) Can be used to filter networks by labels. The response will only contain networks matching the label selector.

ReturnsList[*BoundNetwork*]**get_by_id**(id: int) → *BoundNetwork*

Get a specific network

Parameters**id** – int**Returns***BoundNetwork***get_by_name**(name: str) → *BoundNetwork* | None

Get network by name

Parameters**name** – str Used to get network by name.**Returns***BoundNetwork***get_list**(name: str | None = None, label_selector: str | None = None, page: int | None = None, per_page: int | None = None) → NetworksPageResult

Get a list of networks from this account

Parameters

- **name** – str (optional) Can be used to filter networks by their name.
- **label_selector** – str (optional) Can be used to filter networks by labels. The response will only contain networks matching the label selector.
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns(List[[BoundNetwork](#)], Meta)

update(*network*: [Network](#) | [BoundNetwork](#), *name*: str | None = None, *expose_routes_to_vswitch*: bool | None = None, *labels*: dict[str, str] | None = None) → [BoundNetwork](#)

Updates a network. You can update a network's name and a network's labels.

Parameters

- **network** – [BoundNetwork](#) or [Network](#)
- **name** – str (optional) New name to set
- **expose_routes_to_vswitch** – Optional[bool] Indicates if the routes from this network should be exposed to the vSwitch connection. The exposing only takes effect if a vSwitch connection is active.
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)

Returns[BoundNetwork](#)

class [BoundNetwork](#)(*client*: [NetworksClient](#), *data*: dict, *complete*: bool = True)

add_route(*route*: [NetworkRoute](#)) → [BoundAction](#)

Adds a route entry to a network.

Parameters

route – [NetworkRoute](#) The NetworkRoute you want to add to the Network

Returns[BoundAction](#)

add_subnet(*subnet*: [NetworkSubnet](#)) → [BoundAction](#)

Adds a subnet entry to a network.

Parameters

subnet – [NetworkSubnet](#) The NetworkSubnet you want to add to the Network

Returns[BoundAction](#)

change_ip_range(*ip_range*: str) → [BoundAction](#)

Changes the IP range of a network.

Parameters

ip_range – str The new prefix for the whole network.

Returns[BoundAction](#)

change_protection(*delete*: bool | None = None) → [BoundAction](#)

Changes the protection configuration of a network.

Parameters

delete – boolean If True, prevents the network from being deleted

Returns[BoundAction](#)

delete() → bool

Deletes a network.

Returns

boolean

delete_route(*route*: [NetworkRoute](#)) → [BoundAction](#)

Removes a route entry to a network.

Parameters**route** – [NetworkRoute](#) The NetworkRoute you want to remove from the Network**Returns**[BoundAction](#)**delete_subnet**(*subnet*: [NetworkSubnet](#)) → [BoundAction](#)

Removes a subnet entry from a network

Parameters**subnet** – [NetworkSubnet](#) The NetworkSubnet you want to remove from the Network**Returns**[BoundAction](#)**get_actions**(*status*: list[str] | None = None, *sort*: list[str] | None = None) → list[[BoundAction](#)]

Returns all action objects for a network.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

ReturnsList[[BoundAction](#)]**get_actions_list**(*status*: list[str] | None = None, *sort*: list[str] | None = None, *page*: int | None = None, *per_page*: int | None = None) → [ActionsPageResult](#)

Returns all action objects for a network.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns(List[[BoundAction](#)], [Meta](#))**model**alias of [Network](#)

```
update(name: str | None = None, expose_routes_to_vswitch: bool | None = None, labels: dict[str, str] | None = None) → BoundNetwork
```

Updates a network. You can update a network's name and a networks's labels.

Parameters

- **name** – str (optional) New name to set
- **expose_routes_to_vswitch** – Optional[bool] Indicates if the routes from this network should be exposed to the vSwitch connection. The exposing only takes effect if a vSwitch connection is active.
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)

Returns

BoundNetwork

```
class Network(id: int, name: str | None = None, created: str | None = None, ip_range: str | None = None, subnets: list[NetworkSubnet] | None = None, routes: list[NetworkRoute] | None = None, expose_routes_to_vswitch: bool | None = None, servers: list[BoundServer] | None = None, protection: dict | None = None, labels: dict[str, str] | None = None)
```

Network Domain

Parameters

- **id** – int ID of the network
- **name** – str Name of the network
- **ip_range** – str IPv4 prefix of the whole network
- **subnets** – List[*NetworkSubnet*] Subnets allocated in this network
- **routes** – List[*NetworkRoute*] Routes set in this network
- **expose_routes_to_vswitch** – bool Indicates if the routes from this network should be exposed to the vSwitch connection.
- **servers** – List[*BoundServer*] Servers attached to this network
- **protection** – dict Protection configuration for the network
- **labels** – dict User-defined labels (key-value pairs)

```
class NetworkSubnet(ip_range: str, type: str | None = None, network_zone: str | None = None, gateway: str | None = None, vswitch_id: int | None = None)
```

Network Subnet Domain

Parameters

- **type** – str Type of sub network.
- **ip_range** – str Range to allocate IPs from.
- **network_zone** – str Name of network zone.
- **gateway** – str Gateway for the route.
- **vswitch_id** – int ID of the vSwitch.

```
TYPE_CLOUD = 'cloud'
```

Subnet Type cloud

TYPE_SERVER = 'server'

Subnet Type server, deprecated, use TYPE_CLOUD instead

TYPE_VSWITCH = 'vswitch'

Subnet Type vSwitch

class NetworkRoute(*destination: str, gateway: str*)

Network Route Domain

Parameters

- **destination** – str Destination network or host of this route.
- **gateway** – str Gateway for the route.

class CreateNetworkResponse(*network: BoundNetwork, action: BoundAction*)

Create Network Response Domain

Parameters

- **network** – *BoundNetwork* The network which was created
- **action** – *BoundAction* The Action which shows the progress of the network Creation

4.2.12 PlacementGroupsClient

class PlacementGroupsClient(*client: Client*)

create(*name: str, type: str, labels: dict[str, str] | None = None*) → *CreatePlacementGroupResponse*

Creates a new Placement Group.

Parameters

- **name** – str Placement Group Name
- **type** – str Type of the Placement Group
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)

Returns

CreatePlacementGroupResponse

delete(*placement_group: PlacementGroup | BoundPlacementGroup*) → bool

Deletes a Placement Group.

Parameters

placement_group – *BoundPlacementGroup* or *PlacementGroup*

Returns

boolean

get_all(*label_selector: str | None = None, name: str | None = None, sort: list[str] | None = None*) → list[*BoundPlacementGroup*]

Get all Placement Groups

Parameters

- **label_selector** – str (optional) Can be used to filter Placement Groups by labels. The response will only contain Placement Groups matching the label selector values.
- **name** – str (optional) Can be used to filter Placement Groups by their name.

- **sort** – List[str] (optional) Choices: id name created (You can add one of “:asc”, “:desc” to modify sort order. (“:asc” is default))

Returns

List[*BoundPlacementGroup*]

get_by_id(*id: int*) → *BoundPlacementGroup*

Returns a specific Placement Group object

Parameters

id – int

Returns

BoundPlacementGroup

get_by_name(*name: str*) → *BoundPlacementGroup* | None

Get Placement Group by name

Parameters

name – str Used to get Placement Group by name

Returns

class:*BoundPlacementGroup* <*hcloud.placement_groups.client.BoundPlacementGroup*>

get_list(*label_selector: str | None = None, page: int | None = None, per_page: int | None = None, name: str | None = None, sort: list[str] | None = None, type: str | None = None*) → *PlacementGroupsPageResult*

Get a list of Placement Groups

Parameters

- **label_selector** – str (optional) Can be used to filter Placement Groups by labels. The response will only contain Placement Groups matching the label selector values.
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page
- **name** – str (optional) Can be used to filter Placement Groups by their name.
- **sort** – List[str] (optional) Choices: id name created (You can add one of “:asc”, “:desc” to modify sort order. (“:asc” is default))

Returns

(List[*BoundPlacementGroup*], Meta)

update(*placement_group: PlacementGroup | BoundPlacementGroup, labels: dict[str, str] | None = None, name: str | None = None*) → *BoundPlacementGroup*

Updates the description or labels of a Placement Group.

Parameters

- **placement_group** – *BoundPlacementGroup* or *PlacementGroup*
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)
- **name** – str (optional) New name to set

Returns

BoundPlacementGroup

class BoundPlacementGroup(*client: ClientEntityBase, data: dict, complete: bool = True*)

delete() → bool

Deletes a Placement Group

Returns

boolean

model

alias of *PlacementGroup*

update(*labels: dict[str, str] | None = None, name: str | None = None*) → *BoundPlacementGroup*

Updates the name or labels of a Placement Group

Parameters

- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)
- **name** – str, (optional) New Name to set

Returns

BoundPlacementGroup

class PlacementGroup(*id: int | None = None, name: str | None = None, labels: dict[str, str] | None = None, servers: list[int] | None = None, type: str | None = None, created: str | None = None*)

Placement Group Domain

Parameters

- **id** – int ID of the Placement Group
- **name** – str Name of the Placement Group
- **labels** – dict User-defined labels (key-value pairs)
- **servers** – List[int] List of server IDs assigned to the Placement Group
- **type** – str Type of the Placement Group
- **created** – datetime Point in time when the image was created

class CreatePlacementGroupResponse(*placement_group: BoundPlacementGroup, action: BoundAction | None*)

Create Placement Group Response Domain

Parameters

- **placement_group** – *BoundPlacementGroup* The Placement Group which was created
- **action** – *BoundAction* The Action which shows the progress of the Placement Group Creation

4.2.13 PrimaryIPsClient

class PrimaryIPsClient(*client: Client*)

actions: *ResourceActionsClient*

Primary IPs scoped actions client

Type

ResourceActionsClient

assign(primary_ip: PrimaryIP | BoundPrimaryIP, assignee_id: int, assignee_type: str = 'server') → BoundAction

Assigns a Primary IP to a assignee_id.

Parameters

- **primary_ip** – BoundPrimaryIP or PrimaryIP
- **assignee_id** – int Assignee the Primary IP shall be assigned to
- **assignee_type** – str Assignee the Primary IP shall be assigned to

Returns

BoundAction

change_dns_ptr(primary_ip: PrimaryIP | BoundPrimaryIP, ip: str, dns_ptr: str) → BoundAction

Changes the dns ptr that will appear when getting the dns ptr belonging to this Primary IP.

Parameters

- **primary_ip** – BoundPrimaryIP or PrimaryIP
- **ip** – str The IP address for which to set the reverse DNS entry
- **dns_ptr** – str Hostname to set as a reverse DNS PTR entry, will reset to original default value if None

Returns

BoundAction

change_protection(primary_ip: PrimaryIP | BoundPrimaryIP, delete: bool | None = None) → BoundAction

Changes the protection configuration of the Primary IP.

Parameters

- **primary_ip** – BoundPrimaryIP or PrimaryIP
- **delete** – boolean If true, prevents the Primary IP from being deleted

Returns

BoundAction

create(type: str, datacenter: Datacenter | BoundDatacenter | None, name: str, assignee_type: str | None = 'server', assignee_id: int | None = None, auto_delete: bool | None = False, labels: dict | None = None) → CreatePrimaryIPResponse

Creates a new Primary IP assigned to a server.

Parameters

- **type** – str Primary IP type Choices: ipv4, ipv6
- **assignee_type** – str
- **assignee_id** – int (optional)
- **datacenter** – Datacenter
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)
- **name** – str
- **auto_delete** – bool (optional)

Returns

CreatePrimaryIPResponse

delete(*primary_ip*: [PrimaryIP](#) | [BoundPrimaryIP](#)) → bool

Deletes a Primary IP. If it is currently assigned to an assignee it will automatically get unassigned.

Parameters

primary_ip – [BoundPrimaryIP](#) or [PrimaryIP](#)

Returns

boolean

get_all(*label_selector*: str | None = None, *name*: str | None = None) → list[[BoundPrimaryIP](#)]

Get all primary ips from this account

Parameters

- **label_selector** – str (optional) Can be used to filter Primary IPs by labels. The response will only contain Primary IPs matching the label selector.able values.
- **name** – str (optional) Can be used to filter networks by their name.

Returns

List[[BoundPrimaryIP](#)]

get_by_id(*id*: int) → [BoundPrimaryIP](#)

Returns a specific Primary IP object.

Parameters

id – int

Returns

[BoundPrimaryIP](#)

get_by_name(*name*: str) → [BoundPrimaryIP](#) | None

Get Primary IP by name

Parameters

name – str Used to get Primary IP by name.

Returns

[BoundPrimaryIP](#)

get_list(*label_selector*: str | None = None, *page*: int | None = None, *per_page*: int | None = None, *name*: str | None = None, *ip*: str | None = None) → PrimaryIPsPageResult

Get a list of primary ips from this account

Parameters

- **label_selector** – str (optional) Can be used to filter Primary IPs by labels. The response will only contain Primary IPs matching the label selectorable values.
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page
- **name** – str (optional) Can be used to filter networks by their name.
- **ip** – str (optional) Can be used to filter resources by their ip. The response will only contain the resources matching the specified ip.

Returns

(List[[BoundPrimaryIP](#)], Meta)

unassign(primary_ip: PrimaryIP | BoundPrimaryIP) → BoundAction

Unassigns a Primary IP, resulting in it being unreachable. You may assign it to a server again at a later time.

Parameters

primary_ip – BoundPrimaryIP or PrimaryIP

Returns

BoundAction

update(primary_ip: PrimaryIP | BoundPrimaryIP, auto_delete: bool | None = None, labels: dict[str, str] | None = None, name: str | None = None) → BoundPrimaryIP

Updates the name, auto_delete or labels of a Primary IP.

Parameters

- **primary_ip** – BoundPrimaryIP or PrimaryIP
- **auto_delete** – bool (optional) Delete this Primary IP when the resource it is assigned to is deleted
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)
- **name** – str (optional) New name to set

Returns

BoundPrimaryIP

class BoundPrimaryIP(client: PrimaryIPsClient, data: dict, complete: bool = True)

assign(assignee_id: int, assignee_type: str) → BoundAction

Assigns a Primary IP to a assignee.

Parameters

- **assignee_id** – int` Id of an assignee the Primary IP shall be assigned to
- **assignee_type** – string` Assignee type (e.g server) the Primary IP shall be assigned to

Returns

BoundAction

change_dns_ptr(ip: str, dns_ptr: str) → BoundAction

Changes the hostname that will appear when getting the hostname belonging to this Primary IP.

Parameters

- **ip** – str The IP address for which to set the reverse DNS entry
- **dns_ptr** – str Hostname to set as a reverse DNS PTR entry, will reset to original default value if None

Returns

BoundAction

change_protection(delete: bool | None = None) → BoundAction

Changes the protection configuration of the Primary IP.

Parameters

delete – boolean If true, prevents the Primary IP from being deleted

Returns

BoundAction

delete() → bool

Deletes a Primary IP. If it is currently assigned to a server it will automatically get unassigned.

Returns

boolean

model

alias of *PrimaryIP*

unassign() → *BoundAction*

Unassigns a Primary IP, resulting in it being unreachable. You may assign it to a server again at a later time.

Returns

BoundAction

update(*auto_delete: bool | None = None, labels: dict[str, str] | None = None, name: str | None = None*) → *BoundPrimaryIP*

Updates the description or labels of a Primary IP.

Parameters

- **auto_delete** – bool (optional) Auto delete IP when assignee gets deleted
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)
- **name** – str (optional) New Name to set

Returns

BoundPrimaryIP

```
class PrimaryIP(id: int | None = None, type: str | None = None, ip: str | None = None, dns_ptr: list[dict] | None = None, datacenter: BoundDatacenter | None = None, blocked: bool | None = None, protection: dict | None = None, labels: dict[str, dict] | None = None, created: str | None = None, name: str | None = None, assignee_id: int | None = None, assignee_type: str | None = None, auto_delete: bool | None = None)
```

Primary IP Domain

Parameters

- **id** – int ID of the Primary IP
- **ip** – str IP address of the Primary IP
- **type** – str Type of Primary IP. Choices: *ipv4*, *ipv6*
- **dns_ptr** – List[Dict] Array of reverse DNS entries
- **datacenter** – *Datacenter* Datacenter the Primary IP was created in.
- **blocked** – boolean Whether the IP is blocked
- **protection** – dict Protection configuration for the Primary IP
- **labels** – dict User-defined labels (key-value pairs)
- **created** – datetime Point in time when the Primary IP was created
- **name** – str Name of the Primary IP
- **assignee_id** – int Assignee ID the Primary IP is assigned to
- **assignee_type** – str Assignee Type of entity the Primary IP is assigned to
- **auto_delete** – bool Delete the Primary IP when the Assignee it is assigned to is deleted.

4.2.14 ServerTypesClient

class `ServerTypesClient(client: Client)`

get_all(name: str | None = None) → list[*BoundServerType*]

Get all Server types

Parameters

name – str (optional) Can be used to filter server type by their name.

Returns

List[*BoundServerType*]

get_by_id(id: int) → *BoundServerType*

Returns a specific Server Type.

Parameters

id – int

Returns

BoundServerType

get_by_name(name: str) → *BoundServerType* | None

Get Server type by name

Parameters

name – str Used to get Server type by name.

Returns

BoundServerType

get_list(name: str | None = None, page: int | None = None, per_page: int | None = None) → *ServerTypesPageResult*

Get a list of Server types

Parameters

- **name** – str (optional) Can be used to filter server type by their name.
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[*BoundServerType*], *Meta*)

class `BoundServerType(client: ClientEntityBase, data: dict, complete: bool = True)`

model

alias of *ServerType*

class `ServerType(id: int | None = None, name: str | None = None, description: str | None = None, cores: int | None = None, memory: int | None = None, disk: int | None = None, prices: dict | None = None, storage_type: str | None = None, cpu_type: str | None = None, architecture: str | None = None, deprecated: bool | None = None, deprecation: dict | None = None, included_traffic: int | None = None)`

ServerType Domain

Parameters

- **id** – int ID of the server type

- **name** – str Unique identifier of the server type
- **description** – str Description of the server type
- **cores** – int Number of cpu cores a server of this type will have
- **memory** – int Memory a server of this type will have in GB
- **disk** – int Disk size a server of this type will have in GB
- **prices** – Dict Prices in different locations
- **storage_type** – str Type of server boot drive. Local has higher speed. Network has better availability. Choices: *local*, *network*
- **cpu_type** – string Type of cpu. Choices: *shared*, *dedicated*
- **architecture** – string Architecture of cpu. Choices: *x86*, *arm*
- **deprecated** – bool True if server type is deprecated. This field is deprecated. Use *deprecation* instead.
- **deprecation** – *DeprecationInfo*, None Describes if, when & how the resources was deprecated. If this field is set to None the resource is not deprecated. If it has a value, it is considered deprecated.
- **included_traffic** – int Free traffic per month in bytes

4.2.15 ServersClient

class ServersClient(*client*: Client)

actions: *ResourceActionsClient*

Servers scoped actions client

Type

ResourceActionsClient

add_to_placement_group(*server*: Server | BoundServer, *placement_group*: PlacementGroup | BoundPlacementGroup) → *BoundAction*

Adds a server to a placement group.

Parameters

- **server** – *BoundServer* or *Server*
- **placement_group** – *BoundPlacementGroup* or *Network*

Returns

BoundAction

attach_iso(*server*: Server | BoundServer, *iso*: Iso | BoundIso) → *BoundAction*

Attaches an ISO to a server.

Parameters

- **server** – *BoundServer* or *Server*
- **iso** – *BoundIso* or *Server*

Returns

BoundAction

attach_to_network(*server*: [Server](#) | [BoundServer](#), *network*: [Network](#) | [BoundNetwork](#), *ip*: *str* | *None* = *None*, *alias_ips*: *list[str]* | *None* = *None*) → [BoundAction](#)

Attaches a server to a network

Parameters

- **server** – [BoundServer](#) or [Server](#)
- **network** – [BoundNetwork](#) or [Network](#)
- **ip** – str IP to request to be assigned to this server
- **alias_ips** – List[str] New alias IPs to set for this server.

Returns

[BoundAction](#)

change_alias_ips(*server*: [Server](#) | [BoundServer](#), *network*: [Network](#) | [BoundNetwork](#), *alias_ips*: *list[str]*) → [BoundAction](#)

Changes the alias IPs of an already attached network.

Parameters

- **server** – [BoundServer](#) or [Server](#)
- **network** – [BoundNetwork](#) or [Network](#)
- **alias_ips** – List[str] New alias IPs to set for this server.

Returns

[BoundAction](#)

change_dns_ptr(*server*: [Server](#) | [BoundServer](#), *ip*: *str*, *dns_ptr*: *str* | *None*) → [BoundAction](#)

Changes the hostname that will appear when getting the hostname belonging to the primary IPs (ipv4 and ipv6) of this server.

Parameters

- **server** – [BoundServer](#) or [Server](#)
- **ip** – str The IP address for which to set the reverse DNS entry
- **dns_ptr** – Hostname to set as a reverse DNS PTR entry, will reset to original default value if *None*

Returns

[BoundAction](#)

change_protection(*server*: [Server](#) | [BoundServer](#), *delete*: *bool* | *None* = *None*, *rebuild*: *bool* | *None* = *None*) → [BoundAction](#)

Changes the protection configuration of the server.

Parameters

- **server** – [BoundServer](#) or [Server](#)
- **delete** – boolean If true, prevents the server from being deleted (currently delete and rebuild attribute needs to have the same value)
- **rebuild** – boolean If true, prevents the server from being rebuilt (currently delete and rebuild attribute needs to have the same value)

Returns

[BoundAction](#)

change_type(server: [Server](#) | [BoundServer](#), server_type: [ServerType](#) | [BoundServerType](#), upgrade_disk: bool) → [BoundAction](#)

Changes the type (Cores, RAM and disk sizes) of a server.

Parameters

- **server** – [BoundServer](#) or [Server](#)
- **server_type** – [BoundServerType](#) or [ServerType](#) Server type the server should migrate to
- **upgrade_disk** – boolean If false, do not upgrade the disk. This allows downgrading the server type later.

Returns

[BoundAction](#)

create(name: str, server_type: [ServerType](#) | [BoundServerType](#), image: [Image](#), ssh_keys: list[[SSHKey](#) | [BoundSSHKey](#)] | None = None, volumes: list[[Volume](#) | [BoundVolume](#)] | None = None, firewalls: list[[Firewall](#) | [BoundFirewall](#)] | None = None, networks: list[[Network](#) | [BoundNetwork](#)] | None = None, user_data: str | None = None, labels: dict[str, str] | None = None, location: [Location](#) | [BoundLocation](#) | None = None, datacenter: [Datacenter](#) | [BoundDatacenter](#) | None = None, start_after_create: bool | None = True, automount: bool | None = None, placement_group: [PlacementGroup](#) | [BoundPlacementGroup](#) | None = None, public_net: [ServerCreatePublicNetwork](#) | None = None) → [CreateServerResponse](#)

Creates a new server. Returns preliminary information about the server as well as an action that covers progress of creation.

Parameters

- **name** – str Name of the server to create (must be unique per project and a valid hostname as per RFC 1123)
- **server_type** – [BoundServerType](#) or [ServerType](#) Server type this server should be created with
- **image** – [BoundImage](#) or [Image](#) Image the server is created from
- **ssh_keys** – List[[BoundSSHKey](#) or [SSHKey](#)] (optional) SSH keys which should be injected into the server at creation time
- **volumes** – List[[BoundVolume](#) or [Volume](#)] (optional) Volumes which should be attached to the server at the creation time. Volumes must be in the same location.
- **networks** – List[[BoundNetwork](#) or [Network](#)] (optional) Networks which should be attached to the server at the creation time.
- **user_data** – str (optional) Cloud-Init user data to use during server creation. This field is limited to 32KiB.
- **labels** – Dict[str,str] (optional) User-defined labels (key-value pairs)
- **location** – [BoundLocation](#) or [Location](#)
- **datacenter** – [BoundDatacenter](#) or [Datacenter](#)
- **start_after_create** – boolean (optional) Start Server right after creation. Defaults to True.
- **automount** – boolean (optional) Auto mount volumes after attach.
- **placement_group** – [BoundPlacementGroup](#) or [Location](#) Placement Group where server should be added during creation

- **public_net** – *ServerCreatePublicNetwork* Options to configure the public network of a server on creation

Returns*CreateServerResponse*

create_image(*server*: *Server* | *BoundServer*, *description*: *str* | *None* = *None*, *type*: *str* | *None* = *None*, *labels*: *dict*[*str*, *str*] | *None* = *None*) → *CreateImageResponse*

Creates an image (snapshot) from a server by copying the contents of its disks.

Parameters

- **server** – *BoundServer* or *Server*
- **description** – *str* (optional) Description of the image. If you do not set this we auto-generate one for you.
- **type** – *str* (optional) Type of image to create (default: snapshot) Choices: snapshot, backup
- **labels** – *Dict*[*str*, *str*] User-defined labels (key-value pairs)

Returns*CreateImageResponse*

delete(*server*: *Server* | *BoundServer*) → *BoundAction*

Deletes a server. This immediately removes the server from your account, and it is no longer accessible.

Parameters

server – *BoundServer* or *Server*

Returns*BoundAction*

detach_from_network(*server*: *Server* | *BoundServer*, *network*: *Network* | *BoundNetwork*) → *BoundAction*

Detaches a server from a network.

Parameters

- **server** – *BoundServer* or *Server*
- **network** – *BoundNetwork* or *Network*

Returns*BoundAction*

detach_iso(*server*: *Server* | *BoundServer*) → *BoundAction*

Detaches an ISO from a server.

Parameters

server – *BoundServer* or *Server*

Returns*BoundAction*

disable_backup(*server*: *Server* | *BoundServer*) → *BoundAction*

Disables the automatic backup option and deletes all existing Backups for a Server.

Parameters

server – *BoundServer* or *Server*

Returns*BoundAction*

disable_rescue(*server*: *Server* | *BoundServer*) → *BoundAction*

Disables the Hetzner Rescue System for a server.

Parameters

server – *BoundServer* or *Server*

Returns

BoundAction

enable_backup(*server*: *Server* | *BoundServer*) → *BoundAction*

Enables and configures the automatic daily backup option for the server. Enabling automatic backups will increase the price of the server by 20%.

Parameters

server – *BoundServer* or *Server*

Returns

BoundAction

enable_rescue(*server*: *Server* | *BoundServer*, *type*: *str* | *None* = *None*, *ssh_keys*: *list[str]* | *None* = *None*) → *EnableRescueResponse*

Enable the Hetzner Rescue System for this server.

Parameters

- **server** – *BoundServer* or *Server*
- **type** – *str* Type of rescue system to boot (default: *linux64*) Choices: *linux64*, *linux32*, *freebsd64*
- **ssh_keys** – *List[str]* Array of SSH key IDs which should be injected into the rescue system. Only available for types: *linux64* and *linux32*.

Returns

EnableRescueResponse

get_actions(*server*: *Server* | *BoundServer*, *status*: *list[str]* | *None* = *None*, *sort*: *list[str]* | *None* = *None*) → *list[BoundAction]*

Returns all action objects for a server.

Parameters

- **server** – *BoundServer* or *Server*
- **status** – *List[str]* (optional) Response will have only actions with specified statuses. Choices: *running* *success* *error*
- **sort** – *List[str]* (optional) Specify how the results are sorted. Choices: *id* *id:asc* *id:desc* *command* *command:asc* *command:desc* *status* *status:asc* *status:desc* *progress* *progress:asc* *progress:desc* *started* *started:asc* *started:desc* *finished* *finished:asc* *finished:desc*

Returns

List[BoundAction]

get_actions_list(*server*: *Server* | *BoundServer*, *status*: *list[str]* | *None* = *None*, *sort*: *list[str]* | *None* = *None*, *page*: *int* | *None* = *None*, *per_page*: *int* | *None* = *None*) → *ActionsPageResult*

Returns all action objects for a server.

Parameters

- **server** – *BoundServer* or *Server*

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[[BoundAction](#)], Meta)

get_all(name: str | None = None, label_selector: str | None = None, status: list[str] | None = None) → list[[BoundServer](#)]

Get all servers from this account

Parameters

- **name** – str (optional) Can be used to filter servers by their name.
- **label_selector** – str (optional) Can be used to filter servers by labels. The response will only contain servers matching the label selector.
- **status** – List[str] (optional) Can be used to filter servers by their status. The response will only contain servers matching the status.

Returns

List[[BoundServer](#)]

get_by_id(id: int) → [BoundServer](#)

Get a specific server

Parameters

id – int

Returns

[BoundServer](#)

get_by_name(name: str) → [BoundServer](#) | None

Get server by name

Parameters

name – str Used to get server by name.

Returns

[BoundServer](#)

get_list(name: str | None = None, label_selector: str | None = None, page: int | None = None, per_page: int | None = None, status: list[str] | None = None) → ServersPageResult

Get a list of servers from this account

Parameters

- **name** – str (optional) Can be used to filter servers by their name.
- **label_selector** – str (optional) Can be used to filter servers by labels. The response will only contain servers matching the label selector.
- **status** – List[str] (optional) Can be used to filter servers by their status. The response will only contain servers matching the status.

- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns(List[[BoundServer](#)], Meta)

get_metrics(*server*: [Server](#) | [BoundServer](#), *type*: Literal['cpu', 'disk', 'network'] | list[Literal['cpu', 'disk', 'network']], *start*: datetime | str, *end*: datetime | str, *step*: float | None = None) → GetMetricsResponse

Get Metrics for a Server.

Parameters

- **server** – The Server to get the metrics for.
- **type** – Type of metrics to get.
- **start** – Start of period to get Metrics for (in ISO-8601 format).
- **end** – End of period to get Metrics for (in ISO-8601 format).
- **step** – Resolution of results in seconds.

power_off(*server*: [Server](#) | [BoundServer](#)) → [BoundAction](#)

Cuts power to the server. This forcefully stops it without giving the server operating system time to gracefully stop

Parameters

server – [BoundServer](#) or [Server](#)

Returns

[BoundAction](#)

power_on(*server*: [Server](#) | [BoundServer](#)) → [BoundAction](#)

Starts a server by turning its power on.

Parameters

server – [BoundServer](#) or [Server](#)

Returns

[BoundAction](#)

reboot(*server*: [Server](#) | [BoundServer](#)) → [BoundAction](#)

Reboots a server gracefully by sending an ACPI request.

Parameters

server – [BoundServer](#) or [Server](#)

Returns

[BoundAction](#)

rebuild(*server*: [Server](#) | [BoundServer](#), *image*: [Image](#) | [BoundImage](#), *, *return_response*: bool = False) → RebuildResponse | [BoundAction](#)

Rebuilds a server overwriting its disk with the content of an image, thereby destroying all data on the target server.

Parameters

- **server** – Server to rebuild
- **image** – Image to use for the rebuilt server
- **return_response** – Whether to return the full response or only the action.

remove_from_placement_group(*server*: *Server* | *BoundServer*) → *BoundAction*

Removes a server from a placement group.

Parameters

server – *BoundServer* or *Server*

Returns

BoundAction

request_console(*server*: *Server* | *BoundServer*) → *RequestConsoleResponse*

Requests credentials for remote access via vnc over websocket to keyboard, monitor, and mouse for a server.

Parameters

server – *BoundServer* or *Server*

Returns

RequestConsoleResponse

reset(*server*: *Server* | *BoundServer*) → *BoundAction*

Cuts power to a server and starts it again.

Parameters

server – *BoundServer* or *Server*

Returns

BoundAction

reset_password(*server*: *Server* | *BoundServer*) → *ResetPasswordResponse*

Resets the root password. Only works for Linux systems that are running the qemu guest agent.

Parameters

server – *BoundServer* or *Server*

Returns

ResetPasswordResponse

shutdown(*server*: *Server* | *BoundServer*) → *BoundAction*

Shuts down a server gracefully by sending an ACPI shutdown request.

Parameters

server – *BoundServer* or *Server*

Returns

BoundAction

update(*server*: *Server* | *BoundServer*, *name*: *str* | *None* = *None*, *labels*: *dict*[*str*, *str*] | *None* = *None*) → *BoundServer*

Updates a server. You can update a server's name and a server's labels.

Parameters

- **server** – *BoundServer* or *Server*
- **name** – *str* (optional) New name to set
- **labels** – *Dict*[*str*, *str*] (optional) User-defined labels (key-value pairs)

Returns

BoundServer

class BoundServer(*client*: *ServersClient*, *data*: *dict*, *complete*: *bool* = *True*)

add_to_placement_group(*placement_group*: PlacementGroup | BoundPlacementGroup) → BoundAction

Adds a server to a placement group.

Parameters

placement_group – BoundPlacementGroup or Network

Returns

BoundAction

attach_iso(*iso*: Iso | BoundIso) → BoundAction

Attaches an ISO to a server.

Parameters

iso – BoundIso or Server

Returns

BoundAction

attach_to_network(*network*: Network | BoundNetwork, *ip*: str | None = None, *alias_ips*: list[str] | None = None) → BoundAction

Attaches a server to a network

Parameters

- **network** – BoundNetwork or Network
- **ip** – str IP to request to be assigned to this server
- **alias_ips** – List[str] New alias IPs to set for this server.

Returns

BoundAction

change_alias_ips(*network*: Network | BoundNetwork, *alias_ips*: list[str]) → BoundAction

Changes the alias IPs of an already attached network.

Parameters

- **network** – BoundNetwork or Network
- **alias_ips** – List[str] New alias IPs to set for this server.

Returns

BoundAction

change_dns_ptr(*ip*: str, *dns_ptr*: str | None) → BoundAction

Changes the hostname that will appear when getting the hostname belonging to the primary IPs (ipv4 and ipv6) of this server.

Parameters

- **ip** – str The IP address for which to set the reverse DNS entry
- **dns_ptr** – Hostname to set as a reverse DNS PTR entry, will reset to original default value if None

Returns

BoundAction

change_protection(*delete*: bool | None = None, *rebuild*: bool | None = None) → BoundAction

Changes the protection configuration of the server.

Parameters

- **server** – *BoundServer* or *Server*
- **delete** – boolean If true, prevents the server from being deleted (currently delete and rebuild attribute needs to have the same value)
- **rebuild** – boolean If true, prevents the server from being rebuilt (currently delete and rebuild attribute needs to have the same value)

Returns*BoundAction***change_type**(*server_type*: *ServerType* | *BoundServerType*, *upgrade_disk*: *bool*) → *BoundAction*

Changes the type (Cores, RAM and disk sizes) of a server.

Parameters

- **server_type** – *BoundServerType* or *ServerType* Server type the server should migrate to
- **upgrade_disk** – boolean If false, do not upgrade the disk. This allows downgrading the server type later.

Returns*BoundAction***create_image**(*description*: *str* | *None* = *None*, *type*: *str* | *None* = *None*, *labels*: *dict*[*str*, *str*] | *None* = *None*) → *CreateImageResponse*

Creates an image (snapshot) from a server by copying the contents of its disks.

Parameters

- **description** – *str* (optional) Description of the image. If you do not set this we auto-generate one for you.
- **type** – *str* (optional) Type of image to create (default: snapshot) Choices: snapshot, backup
- **labels** – *Dict*[*str*, *str*] User-defined labels (key-value pairs)

Returns*CreateImageResponse***delete**() → *BoundAction*

Deletes a server. This immediately removes the server from your account, and it is no longer accessible.

Returns*BoundAction***detach_from_network**(*network*: *Network* | *BoundNetwork*) → *BoundAction*

Detaches a server from a network.

Parameters**network** – *BoundNetwork* or *Network***Returns***BoundAction***detach_iso**() → *BoundAction*

Detaches an ISO from a server.

Returns*BoundAction*

disable_backup() → *BoundAction*

Disables the automatic backup option and deletes all existing Backups for a Server.

Returns

BoundAction

disable_rescue() → *BoundAction*

Disables the Hetzner Rescue System for a server.

Returns

BoundAction

enable_backup() → *BoundAction*

Enables and configures the automatic daily backup option for the server. Enabling automatic backups will increase the price of the server by 20%.

Returns

BoundAction

enable_rescue(*type: str | None = None, ssh_keys: list[str] | None = None*) → *EnableRescueResponse*

Enable the Hetzner Rescue System for this server.

Parameters

- **type** – str Type of rescue system to boot (default: linux64) Choices: linux64, linux32, freebsd64
- **ssh_keys** – List[str] Array of SSH key IDs which should be injected into the rescue system. Only available for types: linux64 and linux32.

Returns

EnableRescueResponse

get_actions(*status: list[str] | None = None, sort: list[str] | None = None*) → list[*BoundAction*]

Returns all action objects for a server.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

Returns

List[*BoundAction*]

get_actions_list(*status: list[str] | None = None, sort: list[str] | None = None, page: int | None = None, per_page: int | None = None*) → *ActionsPageResult*

Returns all action objects for a server.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[[BoundAction](#)], Meta)

get_metrics(*type*: Literal['cpu', 'disk', 'network'] | list[Literal['cpu', 'disk', 'network']], *start*: datetime | str, *end*: datetime | str, *step*: float | None = None) → GetMetricsResponse

Get Metrics for a Server.

Parameters

- **server** – The Server to get the metrics for.
- **type** – Type of metrics to get.
- **start** – Start of period to get Metrics for (in ISO-8601 format).
- **end** – End of period to get Metrics for (in ISO-8601 format).
- **step** – Resolution of results in seconds.

model

alias of [Server](#)

power_off() → [BoundAction](#)

Cuts power to the server. This forcefully stops it without giving the server operating system time to gracefully stop

Returns

[BoundAction](#)

power_on() → [BoundAction](#)

Starts a server by turning its power on.

Returns

[BoundAction](#)

reboot() → [BoundAction](#)

Reboots a server gracefully by sending an ACPI request.

Returns

[BoundAction](#)

rebuild(*image*: [Image](#) | [BoundImage](#), *, *return_response*: bool = False) → RebuildResponse | [BoundAction](#)

Rebuilds a server overwriting its disk with the content of an image, thereby destroying all data on the target server.

Parameters

- **image** – Image to use for the rebuilt server
- **return_response** – Whether to return the full response or only the action.

remove_from_placement_group() → [BoundAction](#)

Removes a server from a placement group.

Returns

[BoundAction](#)

request_console() → *RequestConsoleResponse*

Requests credentials for remote access via vnc over websocket to keyboard, monitor, and mouse for a server.

Returns

RequestConsoleResponse

reset() → *BoundAction*

Cuts power to a server and starts it again.

Returns

BoundAction

reset_password() → *ResetPasswordResponse*

Resets the root password. Only works for Linux systems that are running the qemu guest agent.

Returns

ResetPasswordResponse

shutdown() → *BoundAction*

Shuts down a server gracefully by sending an ACPI shutdown request.

Returns

BoundAction

update(name: str | None = None, labels: dict[str, str] | None = None) → *BoundServer*

Updates a server. You can update a server's name and a server's labels.

Parameters

- **name** – str (optional) New name to set
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)

Returns

BoundServer

```
class Server(id: int, name: str | None = None, status: str | None = None, created: str | None = None, public_net:
    PublicNetwork | None = None, server_type: BoundServerType | None = None, datacenter:
    BoundDatacenter | None = None, image: BoundImage | None = None, iso: BoundIso | None =
    None, rescue_enabled: bool | None = None, locked: bool | None = None, backup_window: str |
    None = None, outgoing_traffic: int | None = None, ingoing_traffic: int | None = None,
    included_traffic: int | None = None, protection: dict | None = None, labels: dict[str, str] | None =
    None, volumes: list[BoundVolume] | None = None, private_net: list[PrivateNet] | None = None,
    primary_disk_size: int | None = None, placement_group: BoundPlacementGroup | None = None)
```

Server Domain

Parameters

- **id** – int ID of the server
- **name** – str Name of the server (must be unique per project and a valid hostname as per RFC 1123)
- **status** – str Status of the server Choices: *running, initializing, starting, stopping, off, deleting, migrating, rebuilding, unknown*
- **created** – datetime Point in time when the server was created
- **public_net** – *PublicNetwork* Public network information.
- **server_type** – *BoundServerType*
- **datacenter** – *BoundDatacenter*

- **image** – *BoundImage*, None
- **iso** – *BoundIso*, None
- **rescue_enabled** – bool True if rescue mode is enabled: Server will then boot into rescue system on next reboot.
- **locked** – bool True if server has been locked and is not available to user.
- **backup_window** – str, None Time window (UTC) in which the backup will run, or None if the backups are not enabled
- **outgoing_traffic** – int, None Outbound Traffic for the current billing period in bytes
- **ingoing_traffic** – int, None Inbound Traffic for the current billing period in bytes
- **included_traffic** – int Free Traffic for the current billing period in bytes
- **primary_disk_size** – int Size of the primary Disk
- **protection** – dict Protection configuration for the server
- **labels** – dict User-defined labels (key-value pairs)
- **volumes** – List[*BoundVolume*] Volumes assigned to this server.
- **private_net** – List[*PrivateNet*] Private networks information.

STATUS_DELETING = 'deleting'

Server Status deleting

STATUS_INIT = 'initializing'

Server Status initializing

STATUS_MIGRATING = 'migrating'

Server Status migrating

STATUS_OFF = 'off'

Server Status off

STATUS_REBUILDING = 'rebuilding'

Server Status rebuilding

STATUS_RUNNING = 'running'

Server Status running

STATUS_STARTING = 'starting'

Server Status starting

STATUS_STOPPING = 'stopping'

Server Status stopping

STATUS_UNKNOWN = 'unknown'

Server Status unknown

```
class PublicNetwork(ipv4: IPv4Address, ipv6: IPv6Network, floating_ips: list[BoundFloatingIP],
                    primary_ipv4: BoundPrimaryIP | None, primary_ipv6: BoundPrimaryIP | None, firewalls:
                    list[PublicNetworkFirewall] | None = None)
```

Public Network Domain

Parameters

- **ipv4** – *IPv4Address*

- **ipv6** – [IPv6Network](#)
- **floating_ips** – List[[BoundFloatingIP](#)]
- **primary_ipv4** – BoundPrimaryIP
- **primary_ipv6** – BoundPrimaryIP
- **firewalls** – List[PublicNetworkFirewall]

class IPv4Address(ip: str, blocked: bool, dns_ptr: str)

IPv4 Address Domain

Parameters

- **ip** – str The IPv4 Address
- **blocked** – bool Determine if the IP is blocked
- **dns_ptr** – str DNS PTR for the ip

class IPv6Network(ip: str, blocked: bool, dns_ptr: list)

IPv6 Network Domain

Parameters

- **ip** – str The IPv6 Network as CIDR Notation
- **blocked** – bool Determine if the Network is blocked
- **dns_ptr** – dict DNS PTR Records for the Network as Dict
- **network** – str The network without the network mask
- **network_mask** – str The network mask

class CreateServerResponse(server: [BoundServer](#), action: [BoundAction](#), next_actions: list[[BoundAction](#)], root_password: str | None)

Create Server Response Domain

Parameters

- **server** – [BoundServer](#) The created server
- **action** – [BoundAction](#) Shows the progress of the server creation
- **next_actions** – List[[BoundAction](#)] Additional actions like a *start_server* action after the server creation
- **root_password** – str, None The root password of the server if no SSH-Key was given on server creation

class ServerCreatePublicNetwork(ipv4: [PrimaryIP](#) | None = None, ipv6: [PrimaryIP](#) | None = None, enable_ipv4: bool = True, enable_ipv6: bool = True)

Server Create Public Network Domain

Parameters

- **ipv4** – Optional[[PrimaryIP](#)]
- **ipv6** – Optional[[PrimaryIP](#)]
- **enable_ipv4** – bool
- **enable_ipv6** – bool

```
class ResetPasswordResponse(action: BoundAction, root_password: str)
```

Reset Password Response Domain

Parameters

- **action** – *BoundAction* Shows the progress of the server password reset action
- **root_password** – str The root password of the server

```
class EnableRescueResponse(action: BoundAction, root_password: str)
```

Enable Rescue Response Domain

Parameters

- **action** – *BoundAction* Shows the progress of the server enable rescue action
- **root_password** – str The root password of the server in the rescue mode

```
class RequestConsoleResponse(action: BoundAction, wss_url: str, password: str)
```

Request Console Response Domain

Parameters

- **action** – *BoundAction* Shows the progress of the server request console action
- **wss_url** – str URL of websocket proxy to use. This includes a token which is valid for a limited time only.
- **password** – str VNC password to use for this connection. This password only works in combination with a wss_url with valid token.

4.2.16 SSHKeysClient

```
class SSHKeysClient(client: Client)
```

```
create(name: str, public_key: str, labels: dict[str, str] | None = None) → BoundSSHKey
```

Creates a new SSH key with the given name and public_key.

Parameters

- **name** – str
- **public_key** – str Public Key of the SSH Key you want create
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)

Returns

BoundSSHKey

```
delete(ssh_key: SSHKey | BoundSSHKey) → bool
```

Deletes an SSH key. It cannot be used anymore.

Parameters

ssh_key – *BoundSSHKey* or *SSHKey*

Returns

True

```
get_all(name: str | None = None, fingerprint: str | None = None, label_selector: str | None = None) → list[BoundSSHKey]
```

Get all SSH keys from the account

Parameters

- **name** – str (optional) Can be used to filter SSH keys by their name. The response will only contain the SSH key matching the specified name.
- **fingerprint** – str (optional) Can be used to filter SSH keys by their fingerprint. The response will only contain the SSH key matching the specified fingerprint.
- **label_selector** – str (optional) Can be used to filter SSH keys by labels. The response will only contain SSH keys matching the label selector.

ReturnsList[[BoundSSHKey](#)]**get_by_fingerprint**(*fingerprint: str*) → [BoundSSHKey](#) | None

Get ssh key by fingerprint

Parameters**fingerprint** – str Used to get ssh key by fingerprint.**Returns**[BoundSSHKey](#)**get_by_id**(*id: int*) → [BoundSSHKey](#)

Get a specific SSH Key by its ID

Parameters**id** – int**Returns**[BoundSSHKey](#)**get_by_name**(*name: str*) → [BoundSSHKey](#) | None

Get ssh key by name

Parameters**name** – str Used to get ssh key by name.**Returns**[BoundSSHKey](#)**get_list**(*name: str | None = None, fingerprint: str | None = None, label_selector: str | None = None, page: int | None = None, per_page: int | None = None*) → SSHKeysPageResult

Get a list of SSH keys from the account

Parameters

- **name** – str (optional) Can be used to filter SSH keys by their name. The response will only contain the SSH key matching the specified name.
- **fingerprint** – str (optional) Can be used to filter SSH keys by their fingerprint. The response will only contain the SSH key matching the specified fingerprint.
- **label_selector** – str (optional) Can be used to filter SSH keys by labels. The response will only contain SSH keys matching the label selector.
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns(List[[BoundSSHKey](#)], Meta)

update(*ssh_key*: [SSHKey](#) | [BoundSSHKey](#), *name*: *str* | *None* = *None*, *labels*: *dict*[*str*, *str*] | *None* = *None*) → [BoundSSHKey](#)

Updates an SSH key. You can update an SSH key name and an SSH key labels.

Parameters

- **ssh_key** – [BoundSSHKey](#) or [SSHKey](#)
- **name** – *str* (optional) New Description to set
- **labels** – *Dict*[*str*, *str*] (optional) User-defined labels (key-value pairs)

Returns

[BoundSSHKey](#)

class [BoundSSHKey](#)(*client*: *ClientEntityBase*, *data*: *dict*, *complete*: *bool* = *True*)

delete() → *bool*

Deletes an SSH key. It cannot be used anymore. :return: boolean

model

alias of [SSHKey](#)

update(*name*: *str* | *None* = *None*, *labels*: *dict*[*str*, *str*] | *None* = *None*) → [BoundSSHKey](#)

Updates an SSH key. You can update an SSH key name and an SSH key labels.

Parameters

- **description** – *str* (optional) New Description to set
- **labels** – *Dict*[*str*, *str*] (optional) User-defined labels (key-value pairs)

Returns

[BoundSSHKey](#)

class [SSHKey](#)(*id*: *int* | *None* = *None*, *name*: *str* | *None* = *None*, *fingerprint*: *str* | *None* = *None*, *public_key*: *str* | *None* = *None*, *labels*: *dict*[*str*, *str*] | *None* = *None*, *created*: *str* | *None* = *None*)

SSHKey Domain

Parameters

- **id** – *int* ID of the SSH key
- **name** – *str* Name of the SSH key (must be unique per project)
- **fingerprint** – *str* Fingerprint of public key
- **public_key** – *str* Public Key
- **labels** – *Dict* User-defined labels (key-value pairs)
- **created** – *datetime* Point in time when the SSH Key was created

4.2.17 VolumesClient

class `VolumesClient`(*client*: `Client`)

actions: `ResourceActionsClient`

Volumes scoped actions client

Type

`ResourceActionsClient`

attach(*volume*: `Volume` | `BoundVolume`, *server*: `Server` | `BoundServer`, *automount*: `bool` | `None` = `None`) → `BoundAction`

Attaches a volume to a server. Works only if the server is in the same location as the volume.

Parameters

- **volume** – `BoundVolume` or `Volume`
- **server** – `BoundServer` or `Server`
- **automount** – boolean

Returns

`BoundAction`

change_protection(*volume*: `Volume` | `BoundVolume`, *delete*: `bool` | `None` = `None`) → `BoundAction`

Changes the protection configuration of a volume.

Parameters

- **volume** – `BoundVolume` or `Volume`
- **delete** – boolean If True, prevents the volume from being deleted

Returns

`BoundAction`

create(*size*: `int`, *name*: `str`, *labels*: `str` | `None` = `None`, *location*: `Location` | `None` = `None`, *server*: `Server` | `None` = `None`, *automount*: `bool` | `None` = `None`, *format*: `str` | `None` = `None`) → `CreateVolumeResponse`

Creates a new volume attached to a server.

Parameters

- **size** – int Size of the volume in GB
- **name** – str Name of the volume
- **labels** – Dict[str,str] (optional) User-defined labels (key-value pairs)
- **location** – `BoundLocation` or `Location`
- **server** – `BoundServer` or `Server`
- **automount** – boolean (optional) Auto mount volumes after attach.
- **format** – str (optional) Format volume after creation. One of: xfs, ext4

Returns

`CreateVolumeResponse`

delete(*volume*: `Volume` | `BoundVolume`) → `bool`

Deletes a volume. All volume data is irreversibly destroyed. The volume must not be attached to a server and it must not have delete protection enabled.

Parameters

volume – *BoundVolume* or *Volume*

Returns

boolean

detach(*volume*: *Volume* | *BoundVolume*) → *BoundAction*

Detaches a volume from the server it's attached to. You may attach it to a server again at a later time.

Parameters

volume – *BoundVolume* or *Volume*

Returns

BoundAction

get_actions(*volume*: *Volume* | *BoundVolume*, *status*: list[str] | None = None, *sort*: list[str] | None = None) → list[*BoundAction*]

Returns all action objects for a volume.

Parameters

- **volume** – *BoundVolume* or *Volume*
- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

Returns

List[*BoundAction*]

get_actions_list(*volume*: *Volume* | *BoundVolume*, *status*: list[str] | None = None, *sort*: list[str] | None = None, *page*: int | None = None, *per_page*: int | None = None) → *ActionsPageResult*

Returns all action objects for a volume.

Parameters

- **volume** – *BoundVolume* or *Volume*
- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[*BoundAction*], Meta)

get_all(*label_selector*: str | None = None, *status*: list[str] | None = None) → list[*BoundVolume*]

Get all volumes from this account

Parameters

- **label_selector** – Can be used to filter volumes by labels. The response will only contain volumes matching the label selector.
- **status** – List[str] (optional) Can be used to filter volumes by their status. The response will only contain volumes matching the status.

ReturnsList[*BoundVolume*]**get_by_id**(*id*: int) → *BoundVolume*

Get a specific volume by its id

Parameters**id** – int**Returns***BoundVolume***get_by_name**(*name*: str) → *BoundVolume* | None

Get volume by name

Parameters**name** – str Used to get volume by name.**Returns***BoundVolume***get_list**(*name*: str | None = None, *label_selector*: str | None = None, *page*: int | None = None, *per_page*: int | None = None, *status*: list[str] | None = None) → VolumesPageResult

Get a list of volumes from this account

Parameters

- **name** – str (optional) Can be used to filter volumes by their name.
- **label_selector** – str (optional) Can be used to filter volumes by labels. The response will only contain volumes matching the label selector.
- **status** – List[str] (optional) Can be used to filter volumes by their status. The response will only contain volumes matching the status.
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns(List[*BoundVolume*], Meta)**resize**(*volume*: *Volume* | *BoundVolume*, *size*: int) → *BoundAction*

Changes the size of a volume. Note that downsizing a volume is not possible.

Parameters

- **volume** – *BoundVolume* or *Volume*
- **size** – int New volume size in GB (must be greater than current size)

Returns*BoundAction***update**(*volume*: *Volume* | *BoundVolume*, *name*: str | None = None, *labels*: dict[str, str] | None = None) → *BoundVolume*

Updates the volume properties.

Parameters

- **volume** – *BoundVolume* or *Volume*
- **name** – str (optional) New volume name
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)

Returns*BoundAction***class** *BoundVolume*(*client*: *VolumesClient*, *data*: dict, *complete*: bool = True)**attach**(*server*: *Server* | *BoundServer*, *automount*: bool | None = None) → *BoundAction*

Attaches a volume to a server. Works only if the server is in the same location as the volume.

Parameters

- **server** – *BoundServer* or *Server*
- **automount** – boolean

Returns*BoundAction***change_protection**(*delete*: bool | None = None) → *BoundAction*

Changes the protection configuration of a volume.

Parameters**delete** – boolean If True, prevents the volume from being deleted**Returns***BoundAction***delete**() → bool

Deletes a volume. All volume data is irreversibly destroyed. The volume must not be attached to a server and it must not have delete protection enabled.

Returns

boolean

detach() → *BoundAction*

Detaches a volume from the server it's attached to. You may attach it to a server again at a later time.

Returns*BoundAction***get_actions**(*status*: list[str] | None = None, *sort*: list[str] | None = None) → list[*BoundAction*]

Returns all action objects for a volume.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*

ReturnsList[*BoundAction*]

get_actions_list(*status: list[str] | None = None, sort: list[str] | None = None, page: int | None = None, per_page: int | None = None*) → *ActionsPageResult*

Returns all action objects for a volume.

Parameters

- **status** – List[str] (optional) Response will have only actions with specified statuses. Choices: *running success error*
- **sort** – List[str] (optional) Specify how the results are sorted. Choices: *id id:asc id:desc command command:asc command:desc status status:asc status:desc progress progress:asc progress:desc started started:asc started:desc finished finished:asc finished:desc*
- **page** – int (optional) Specifies the page to fetch
- **per_page** – int (optional) Specifies how many results are returned by page

Returns

(List[[BoundAction](#)], Meta)

model

alias of [Volume](#)

resize(*size: int*) → [BoundAction](#)

Changes the size of a volume. Note that downsizing a volume is not possible.

Parameters

- **size** – int New volume size in GB (must be greater than current size)

Returns

[BoundAction](#)

update(*name: str | None = None, labels: dict[str, str] | None = None*) → [BoundVolume](#)

Updates the volume properties.

Parameters

- **name** – str (optional) New volume name
- **labels** – Dict[str, str] (optional) User-defined labels (key-value pairs)

Returns

[BoundAction](#)

class Volume(*id: int, name: str | None = None, server: [Server](#) | [BoundServer](#) | None = None, created: str | None = None, location: [Location](#) | [BoundLocation](#) | None = None, size: int | None = None, linux_device: str | None = None, format: str | None = None, protection: dict | None = None, labels: dict[str, str] | None = None, status: str | None = None*)

Volume Domain

Parameters

- **id** – int ID of the Volume
- **name** – str Name of the Volume
- **server** – [BoundServer](#), None Server the Volume is attached to, None if it is not attached at all.
- **created** – datetime Point in time when the Volume was created
- **location** – [BoundLocation](#) Location of the Volume. Volume can only be attached to Servers in the same location.

- **size** – int Size in GB of the Volume
- **linux_device** – str Device path on the file system for the Volume
- **protection** – dict Protection configuration for the Volume
- **labels** – dict User-defined labels (key-value pairs)
- **status** – str Current status of the volume Choices: *creating*, *available*
- **format** – str, None Filesystem of the volume if formatted on creation, None if not formatted on creation.

STATUS_AVAILABLE = 'available'

Volume Status available

STATUS_CREATING = 'creating'

Volume Status creating

class CreateVolumeResponse(volume: [BoundVolume](#), action: [BoundAction](#), next_actions: list[[BoundAction](#)])

Create Volume Response Domain

Parameters

- **volume** – [BoundVolume](#) The created volume
- **action** – [BoundAction](#) The action that shows the progress of the Volume Creation
- **next_actions** – List[[BoundAction](#)] List of actions that are performed after the creation, like attaching to a server

4.3 Exceptions

class HCloudException

There was an error while using the hcloud library

class APIException(code: int | str, message: str | None, details: Any)

There was an error while performing an API Request

class ActionException(action: [Action](#) | [BoundAction](#))

A generic action exception

class ActionFailedException(action: [Action](#) | [BoundAction](#))

The pending action failed

class ActionTimeoutException(action: [Action](#) | [BoundAction](#))

The pending action timed out

4.4 Other

4.4.1 Helpers

class LabelValidator

static validate(*labels: dict[str, str]*) → bool

Validates Labels. If you want to know which key/value pair of the dict is not correctly formatted use `validate_verbose()`.

Returns

bool

static validate_verbose(*labels: dict[str, str]*) → tuple[bool, str]

Validates Labels and returns the corresponding error message if something is wrong. Returns True, <empty string> if everything is fine.

Returns

bool, str

4.4.2 Deprecation Info

class DeprecationInfo(*announced: str | None = None, unavailable_after: str | None = None*)

Describes if, when & how the resources was deprecated. If this field is set to `None` the resource is not deprecated. If it has a value, it is considered deprecated.

Parameters

- **announced** – datetime Date of when the deprecation was announced.
- **unavailable_after** – datetime After the time in this field, the resource will not be available from the general listing endpoint of the resource type, and it can not be used in new resources. For example, if this is an image, you can not create new servers with this image after the mentioned date.

CONTRIBUTING

Contributions are welcome, and they are greatly appreciated! Every little bit helps, and credit will always be given. You can contribute in many ways:

5.1 Types of Contributions

5.1.1 Report Bugs

Report bugs at <https://github.com/hetznercloud/hcloud-python/issues>.

If you are reporting a bug, please include:

- Your operating system name and version.
- Any details about your local setup that might be helpful in troubleshooting.
- Detailed steps to reproduce the bug.

5.1.2 Fix Bugs

Look through the GitHub issues for bugs. Anything tagged with “bug” and “help wanted” is open to whoever wants to implement it.

5.1.3 Implement Features

Look through the GitHub issues for features. Anything tagged with “enhancement” and “help wanted” is open to whoever wants to implement it.

5.1.4 Write Documentation

Hetzner Cloud Python could always use more documentation, whether as part of the official Hetzner Cloud Python docs, in docstrings, or even on the web in blog posts, articles, and such.

5.1.5 Submit Feedback

The best way to send feedback is to file an issue at <https://github.com/hetznercloud/hcloud-python/issues>.

If you are proposing a feature:

- Explain in detail how it would work.
- Keep the scope as narrow as possible, to make it easier to implement.
- Remember that this is a volunteer-driven project, and that contributions are welcome :)

5.2 Get Started!

Ready to contribute? Here's how to set up `hcloud-python` for local development.

1. Fork the `hcloud-python` repo on GitHub.
2. Clone your fork locally:

```
$ git clone git@github.com:your_name_here/hcloud-python.git
```

3. Read the `Development` section in the `README.md`, to setup your development environment.
4. Create a branch for local development:

```
$ git checkout -b name-of-your-bugfix-or-feature
```

Now you can make your changes locally.

5. Commit your changes and push your branch to GitHub:

```
$ git add .  
$ git commit -m "Your detailed description of your changes."  
$ git push origin name-of-your-bugfix-or-feature
```

6. Submit a pull request through the GitHub website.

5.3 Pull Request Guidelines

Before you submit a pull request, check that it meets these guidelines:

1. The pull request should include tests.
2. If the pull request adds functionality, the docs should be updated. Put your new functionality into a function with a docstring, and add the feature to the list in `README.md`.
3. The pull request should work for all the versions of Python the library supports, and for PyPy.

CHANGELOG

6.1 1.35.0 (2024-04-02)

6.1.1 Features

- add `include_deprecated` option when fetching images by name (#375) (6d86f86)

6.1.2 Bug Fixes

- raise warnings for the `ImagesClient.get_by_name` deprecation (#376) (b24de80)

6.2 1.34.0 (2024-03-27)

6.2.1 Features

- add `has_id_or_name` to `DomainIdentityMixin` (#373) (8facaf6)

6.3 1.33.3 (2024-03-27)

6.3.1 Bug Fixes

- invalid type for load balancer private network property (#372) (903e92f)

6.3.2 Dependencies

- update codecov/codecov-action action to v4 (#359) (a798979)
- update dependency mypy to `>=1.9,<1.10` (#368) (4b9328c)
- update dependency pylint to `>=3,<3.2` (#364) (d71d17f)
- update dependency pytest to `>=8,<8.2` (#366) (8665dcf)
- update dependency pytest to v8 (#357) (f8f756f)
- update dependency pytest-cov to v5 (#371) (04a6a42)
- update dependency watchdog to v4 (#360) (cb8d383)

- update pre-commit hook asottile/pyupgrade to v3.15.1 (#362) (dd2a521)
- update pre-commit hook asottile/pyupgrade to v3.15.2 (3d02ad7)
- update pre-commit hook psf/black-pre-commit-mirror to v24 (#356) (b46397d)
- update pre-commit hook psf/black-pre-commit-mirror to v24.1.1 (#358) (7e4645e)
- update pre-commit hook psf/black-pre-commit-mirror to v24.2.0 (#361) (5b56ace)
- update pre-commit hook psf/black-pre-commit-mirror to v24.3.0 (3bbac5d)
- update pre-commit hook pycqa/flake8 to v7 (#354) (66a582f)
- update pypa/gh-action-pypi-publish action to v1.8.12 (#365) (55db255)
- update pypa/gh-action-pypi-publish action to v1.8.14 (#367) (0cb615f)

6.4 1.33.2 (2024-01-02)

6.4.1 Bug Fixes

- publish package to PyPI using OIDC auth (1a0e93b)

6.5 1.33.1 (2024-01-02)

6.5.1 Bug Fixes

- private object not exported in top level module (#346) (5281b05)

6.5.2 Dependencies

- update dependency coverage to $\geq 7.4, < 7.5$ (#348) (3ac5711)
- update dependency mypy to $\geq 1.8, < 1.9$ (#343) (984022f)
- update pre-commit hook psf/black-pre-commit-mirror to v23.12.1 (#347) (2c24efe)

6.6 1.33.0 (2023-12-19)

6.6.1 Features

- add metrics endpoint for load balancers and servers (#331) (ee3c54f)

6.6.2 Bug Fixes

- fallback to error code when message is unset (#328) (1c94153)

6.6.3 Dependencies

- update actions/setup-python action to v5 (#335) (2ac252d)
- update dependency sphinx-rtd-theme to v2 (#330) (7cc4335)
- update pre-commit hook psf/black-pre-commit-mirror to v23.12.0 (#338) (38e4748)
- update pre-commit hook pycqa/isort to v5.13.0 (#336) (3244cfe)
- update pre-commit hook pycqa/isort to v5.13.1 (#337) (020a0ef)
- update pre-commit hook pycqa/isort to v5.13.2 (#339) (b46df8c)

6.7 1.32.0 (2023-11-17)

6.7.1 Features

- allow returning root_password in servers rebuild (#276) (38e098a)

6.7.2 Dependencies

- update dependency mypy to >=1.7,<1.8 (#325) (7b59a2d)
- update pre-commit hook pre-commit/mirrors-prettier to v3.1.0 (#326) (213b661)
- update pre-commit hook psf/black-pre-commit-mirror to v23.10.1 (#322) (999afe3)
- update pre-commit hook psf/black-pre-commit-mirror to v23.11.0 (#324) (7b2a24e)

6.8 1.31.0 (2023-10-23)

6.8.1 Features

- prepare for iso deprecated field removal (#320) (beae328)

6.8.2 Dependencies

- update pre-commit hook psf/black-pre-commit-mirror to v23.10.0 (#319) (184bbe6)

6.9 1.30.0 (2023-10-13)

6.9.1 Features

- add deprecation field to Iso (#318) (036b52f)
- support python 3.12 (#311) (7e8cd1d)

6.9.2 Dependencies

- update dependency mypy to $\geq 1.6, < 1.7$ (#317) (d248bbd)
- update dependency pylint to v3 (#307) (277841d)
- update pre-commit hook asottile/pyupgrade to v3.14.0 (#308) (07a4513)
- update pre-commit hook asottile/pyupgrade to v3.15.0 (#312) (c544639)
- update pre-commit hook pre-commit/pre-commit-hooks to v4.5.0 (#313) (e51eaa9)
- update python docker tag to v3.12 (#309) (3a1ee67)

6.10 1.29.1 (2023-09-26)

6.10.1 Bug Fixes

- prevent api calls when printing bound models (#305) (c1de7ef)

6.11 1.29.0 (2023-09-25)

6.11.1 Features

- add domain attribute type hints to bound models (#300) (6d46d06)
- **firewalls:** add `applied_to_resources` to `FirewallResource` (#297) (55d2b20)

6.11.2 Bug Fixes

- missing `BaseDomain` base class inheritance (#303) (0ee7598)

6.11.3 Dependencies

- update actions/checkout action to v4 (#295) (c02b446)
- update dependency sphinx to $\geq 7.2.2, < 7.3$ (#291) (10234ea)
- update dependency sphinx to v7 (#211) (f635c94)
- update pre-commit hook asottile/pyupgrade to v3.11.0 (#298) (4bbd0cc)
- update pre-commit hook asottile/pyupgrade to v3.11.1 (#299) (2f9fcd7)

- update pre-commit hook asottile/pyupgrade to v3.13.0 (#301) (951dbf3)
- update pre-commit hook pre-commit/mirrors-prettier to v3.0.3 (#294) (381e336)
- update pre-commit hook psf/black to v23.9.1 (#296) (4374a7b)

6.11.4 Documentation

- load token from env in examples scripts (#302) (f18c9a6)

6.12 1.28.0 (2023-08-17)

6.12.1 Features

- add load balancer target health status field (#288) (5780418)
- implement resource actions clients (#252) (4bb9a97)

6.12.2 Dependencies

- update dependency coverage to $\geq 7.3, < 7.4$ (#286) (a4df4fa)
- update dependency mypy to $\geq 1.5, < 1.6$ (#284) (9dd5c81)
- update pre-commit hook pre-commit/mirrors-prettier to v3.0.2 (#287) (6bf03cb)

6.12.3 Documentation

- fail on warning (#289) (e61300e)

6.13 1.27.2 (2023-08-09)

6.13.1 Documentation

- fix python references (#281) (0c0518e)

6.14 1.27.1 (2023-08-08)

6.14.1 Bug Fixes

- missing long_description content_type in setup.py (#279) (6d79d1d)

6.15 1.27.0 (2023-08-08)

6.15.1 Features

- add global request timeout option (#271) (07a663f)
- reexport references in parent resources modules (#256) (854c12b)
- the package is now typed (#265) (da8baa5)

6.15.2 Bug Fixes

- allow omitting `datacenter` when creating a primary ip (#171) (4375dc6)
- ineffective doc strings (#266) (bb34df9)
- invalid attribute in placement group (#258) (23b3607)

6.15.3 Dependencies

- update pre-commit hook asottile/pyupgrade to v3.10.1 (#261) (efa5780)
- update pre-commit hook pre-commit/mirrors-prettier to v3.0.1 (#269) (2239b0b)
- update pre-commit hook pycqa/flake8 to v6.1.0 (#260) (fd01384)

6.15.4 Documentation

- update documentation (#247) (e63741f)
- update hetzner logo (#264) (ee79851)

6.16 1.26.0 (2023-07-19)

6.16.1 Features

- add `repr` method to domains (#246) (4c22765)
- drop support for python 3.7 (#242) (2ce71e9)

6.17 1.25.0 (2023-07-14)

6.17.1 Features

- add details to raise exceptions (#240) (cf64e54)
- move `hcloud.hcloud` module to `hcloud._client` (#243) (413472d)

6.17.2 Dependencies

- update pre-commit hook asottile/pyupgrade to v3.9.0 (#238) (0053ded)
- update pre-commit hook pre-commit/mirrors-prettier to v3 (#235) (047d4e1)
- update pre-commit hook psf/black to v23.7.0 (#239) (443bf26)

6.18 1.24.0 (2023-07-03)

6.18.1 Features

- revert remove python-dateutil dependency (#231) (945bfde), closes #226

6.18.2 Dependencies

- update pre-commit hook asottile/pyupgrade to v3.8.0 (#232) (27f21bc)

6.19 1.23.1 (2023-06-30)

6.19.1 Bug Fixes

- handle Z timezone in ISO8601 datetime format (#228) (6a5c3f4), closes #226

6.20 1.23.0 (2023-06-26)

6.20.1 Features

- remove python-dateutil dependency (#221) (8ea4aa0)

6.20.2 Bug Fixes

- **isos:** invalid name for include_wildcard_architecture argument (#222) (c3dfcab)

6.20.3 Dependencies

- update dependency pytest to >=7.4,<7.5 (#217) (11e1f45)

6.21 1.22.0 (2023-06-22)

6.21.1 Features

- adhere to PEP 517 (#213) (7a19add)
- bump required python version to ≥ 3.7 (#198) (62d89f9)
- **network:** add field `expose_routes_to_vswitch` (#208) (5321182)
- setup exception hierarchy (#199) (8466645)

6.21.2 Dependencies

- update actions/setup-python action to v4 (#209) (aeec575)
- update actions/stale action to v8 (#210) (cb13230)
- update pre-commit hook asottile/pyupgrade to v3.7.0 (#205) (c46c5a4)

6.22 1.21.0 (2023-06-19)

6.22.1 Features

- add deprecation field to `ServerType` (#192) (4a0fce7)

6.22.2 Bug Fixes

- adjust label validation for max length of 63 characters (#194) (3cba96d)

6.22.3 Documentation

- improve branding, design & fix warnings (#191) (47eb9f1)
- use `venv` for the dev setup (#196) (93f48ff)

6.23 1.20.0 (2023-05-12)

6.23.1 Features

- **server_type:** add field for included traffic (#185) (8ae0bc6)

6.24 v1.19.0 (2023-04-12)

- docs: link to PrivateNet broken by @apricote in #177
- feat: add support for ARM APIs by @apricote in #182

6.25 v1.18.2 (2022-12-27)

- fix: remove unused future dependency by @apricote in #173
- chore: update tests to use released python-3.11 by @apricote in #175
- chore: prepare release 1.18.2 by @apricote in #174

v1.18.1 (2022-10-25)

- Update Github Actions by @LKaemmerling in #165
- Add tests for Python 3.11 by @LKaemmerling in #167

6.26 v1.18.0 (2022-08-17)

- Remove use of external mock module by @s-t-e-v-e-n-k in #162
- document installation path via conda-forge by @s-m-e in #149
- Drop # – coding: utf-8 – from files by @jonasdlindner in #154
- Simplify Requirement Constraints by @LKaemmerling in #163
- Add validation helper for Label Values/Keys by @LKaemmerling in #164

6.27 v1.17.0 (2022-06-29)

- Add primary IP support by @LKaemmerling in #160

6.28 v1.16.0 (2021-08-17)

- Feature: Add support for Load Balancer DNS PTRs

6.29 v1.15.0 (2021-08-16)

- Feature: Add support for Placement Groups

6.30 v1.14.1 (2021-08-10)

- Bugfix: Fix crash on extra fields in public_net response
- Improvement: Format code with black

6.31 v1.14.0 (2021-08-03)

- Feature: Add support for Firewall rule descriptions

6.32 v1.13.0 (2021-07-16)

- Feature: Add support for Firewall Protocols ESP and GRE
- Feature: Add support for Image Type APP
- Feature: Add support for creating Firewalls with Firewalls
- Feature: Add support for Label Selectors in Firewalls
- Improvement: Improve handling of underlying TCP connections. Now for every client instance a single TCP connection is used instead of one per call.
- Note: Support for Python 2.7 and Python 3.5 was removed

6.33 v1.12.0 (2021-04-06)

- Feature: Add support for managed Certificates

6.34 v1.11.0 (2021-03-11)

- Feature: Add support for Firewalls
- Feature: Add primary_disk_size to Server Domain

6.35 v1.10.0 (2020-11-03)

- Feature: Add include_deprecated filter to get_list and get_all on ImagesClient
- Feature: Add vSwitch support to add_subnet on NetworksClient
- Feature: Add subnet type constants to NetworkSubnet domain (NetworkSubnet.TYPE_CLOUD, NetworkSubnet.TYPE_VSWITCH)

6.36 v1.9.1 (2020-08-11)

- Bugfix: BoundLoadBalancer serialization failed when using IP targets

6.37 v1.9.0 (2020-08-10)

- Feature: Add `included_traffic`, `outgoing_traffic` and `ingoing_traffic` properties to Load Balancer domain
- Feature: Add `change_type`-method to `LoadBalancersClient`
- Feature: Add support for `LoadBalancerTargetLabelSelector`
- Feature: Add support for `LoadBalancerTargetLabelSelector`

6.38 v1.8.2 (2020-07-20)

- Fix: Loosen up the requirements.

6.39 v1.8.1 (2020-06-29)

- Fix Load Balancer Client.
- Fix: Unify setting of request parameters within `get_list` methods.

6.40 1.8.0 (2020-06-22)

- Feature: Add Load Balancers **Attention: The Load Balancer support in v1.8.0 is kind of broken. Please use v1.8.1**
- Feature: Add Certificates

6.41 1.7.1 (2020-06-15)

- Feature: Add requests 2.23 support

6.42 1.7.0 (2020-06-05)

- Feature: Add support for the optional 'networks' parameter on server creation.
- Feature: Add python 3.9 support
- Feature: Add subnet type `ccloud`

6.43 1.6.3 (2020-01-09)

- Feature: Add ‘created’ property to SSH Key domain
- Fix: Remove ISODateTime Descriptor because it leads to wrong dates

6.44 1.6.2 (2019-10-15)

- Fix: future dependency requirement was too strict

6.45 1.6.1 (2019-10-01)

- Fix: python-dateutil dependency requirement was too strict

6.46 1.6.0 (2019-09-17)

- Feature: Add missing get_by_name on FloatingIPsClient

6.47 1.5.0 (2019-09-16)

- Fix: ServersClient.create_image fails when specifying the labels
- Feature: Add support for name on Floating IPs

6.48 1.4.1 (2019-08-19)

- Fix: Documentation for NetworkRoute domain was missing
- Fix: requests dependency requirement was too strict

6.49 1.4.0 (2019-07-29)

- Feature: Add mac_address to Server PrivateNet domain
- Feature: Add python 3.8 support

6.50 1.3.0 (2019-07-10)

- Feature: Add status filter for servers, images and volumes
- Feature: Add ‘created’ property to Floating IP domain
- Feature: Add ‘Networks’ support

6.51 1.2.1 (2019-03-13)

- Fix: BoundVolume.server server property now casted to the ‘BoundServer’.

6.52 1.2.0 (2019-03-06)

- Feature: Add `get_by_fingerprint`-method for ssh keys
- Fix: Create Floating IP with location raises an error because no action was given.

6.53 1.1.0 (2019-02-27)

- Feature: Add STATUS-constants for server and volume status

6.54 1.0.1 (2019-02-22)

Fix: Ignore unknown fields in API response instead of raising an error

6.55 1.0.0 (2019-02-21)

- First stable release.

You can find the documentation under <https://hcloud-python.readthedocs.io/en/latest/>

6.56 0.1.0 (2018-12-20)

- First release on GitHub.

HETZNER CLOUD PYTHON

Official Hetzner Cloud python library.

The library's documentation is available at hcloud-python.readthedocs.io, the public API documentation is available at docs.hetzner.cloud.

7.1 Usage

Install the hcloud library:

```
pip install hcloud
```

For more installation details, please see the [installation docs](#).

Here is an example that creates a server and list them:

```
from hcloud import Client
from hcloud.images import Image
from hcloud.server_types import ServerType

client = Client(token="{YOUR_API_TOKEN}") # Please paste your API token here

# Create a server named my-server
response = client.servers.create(
    name="my-server",
    server_type=ServerType(name="cx11"),
    image=Image(name="ubuntu-22.04"),
)
server = response.server
print(f"{server.id=} {server.name=} {server.status=}")
print(f"root password: {response.root_password}")

# List your servers
servers = client.servers.get_all()
for server in servers:
    print(f"{server.id=} {server.name=} {server.status=}")
```

For more details, please see the [API reference](#).

You can find some more examples under the [examples/](#) directory.

7.2 Supported Python versions

We support python versions until [end-of-life](#).

7.3 Development

First, create a virtual environment and activate it:

```
make venv
source venv/bin/activate
```

You may setup `pre-commit` to run before you commit changes, this removes the need to run it manually afterwards:

```
pre-commit install
```

You can then run different tasks defined in the `Makefile`, below are the most important ones:

Build the documentation and open it in your browser:

```
make docs
```

Lint the code:

```
make lint
```

Run tests using the current `python3` version:

```
make test
```

You may also run the tests for multiple `python3` versions using `tox`:

```
tox .
```

7.3.1 Deprecations implementation

When deprecating a module or a function, you must:

- Update the docstring with a deprecated notice:

```
"""Get image by name

.. deprecated:: 1.19
   Use :func:`hcloud.images.client.ImagesClient.get_by_name_and_architecture` instead.
"""
```

- Raise a warning when the deprecated module or function is being used:

```
warnings.warn(
    "The 'hcloud.images.client.ImagesClient.get_by_name' method is deprecated, please_
    ↪ use the "
    "'hcloud.images.client.ImagesClient.get_by_name_and_architecture' method instead.",
    DeprecationWarning,
```

(continues on next page)

(continued from previous page)

```
stacklevel=2,  
)
```

7.4 License

The MIT License (MIT). Please see [License File](#) for more information.

A

Action (class in *hcloud.actions.domain*), 10
 ActionException (class in *hcloud.actions.domain*), 86
 ActionFailedException (class in *hcloud.actions.domain*), 86
 actions (CertificatesClient attribute), 11
 actions (Client attribute), 7
 actions (FirewallsClient attribute), 17
 actions (FloatingIPsClient attribute), 22
 actions (ImagesClient attribute), 28
 actions (LoadBalancersClient attribute), 36
 actions (NetworksClient attribute), 48
 actions (PrimaryIPsClient attribute), 57
 actions (ServersClient attribute), 63
 actions (VolumesClient attribute), 81
 ActionsClient (class in *hcloud.actions.client*), 10
 ActionTimeoutException (class in *hcloud.actions.domain*), 86
 add_route() (BoundNetwork method), 52
 add_route() (NetworksClient method), 48
 add_service() (BoundLoadBalancer method), 41
 add_service() (LoadBalancersClient method), 36
 add_subnet() (BoundNetwork method), 52
 add_subnet() (NetworksClient method), 49
 add_target() (BoundLoadBalancer method), 41
 add_target() (LoadBalancersClient method), 36
 add_to_placement_group() (BoundServer method), 70
 add_to_placement_group() (ServersClient method), 63
 APIException (class in *hcloud*), 86
 apply_to_resources() (BoundFirewall method), 19
 apply_to_resources() (FirewallsClient method), 17
 assign() (BoundFloatingIP method), 26
 assign() (BoundPrimaryIP method), 60
 assign() (FloatingIPsClient method), 22
 assign() (PrimaryIPsClient method), 57
 attach() (BoundVolume method), 84
 attach() (VolumesClient method), 81
 attach_iso() (BoundServer method), 71
 attach_iso() (ServersClient method), 63
 attach_to_network() (BoundLoadBalancer method),

42

attach_to_network() (BoundServer method), 71
 attach_to_network() (LoadBalancersClient method), 36
 attach_to_network() (ServersClient method), 63

B

BoundAction (class in *hcloud.actions.client*), 10
 BoundCertificate (class in *hcloud.certificates.client*), 14
 BoundDatacenter (class in *hcloud.datacenters.client*), 16
 BoundFirewall (class in *hcloud.firewalls.client*), 19
 BoundFloatingIP (class in *hcloud.floating_ips.client*), 26
 BoundImage (class in *hcloud.images.client*), 31
 BoundIso (class in *hcloud.isos.client*), 34
 BoundLoadBalancer (class in *hcloud.load_balancers.client*), 41
 BoundLocation (class in *hcloud.locations.client*), 48
 BoundNetwork (class in *hcloud.networks.client*), 52
 BoundPlacementGroup (class in *hcloud.placement_groups.client*), 56
 BoundPrimaryIP (class in *hcloud.primary_ips.client*), 60
 BoundServer (class in *hcloud.servers.client*), 70
 BoundServerType (class in *hcloud.server_types.client*), 62
 BoundSSHKey (class in *hcloud.ssh_keys.client*), 80
 BoundVolume (class in *hcloud.volumes.client*), 84

C

Certificate (class in *hcloud.certificates.domain*), 15
 certificates (Client attribute), 7
 CertificatesClient (class in *hcloud.certificates.client*), 11
 change_algorithm() (BoundLoadBalancer method), 42
 change_algorithm() (LoadBalancersClient method), 36
 change_alias_ips() (BoundServer method), 71
 change_alias_ips() (ServersClient method), 64

- `change_dns_ptr()` (*BoundFloatingIP method*), 26
- `change_dns_ptr()` (*BoundLoadBalancer method*), 42
- `change_dns_ptr()` (*BoundPrimaryIP method*), 60
- `change_dns_ptr()` (*BoundServer method*), 71
- `change_dns_ptr()` (*FloatingIPsClient method*), 23
- `change_dns_ptr()` (*LoadBalancersClient method*), 37
- `change_dns_ptr()` (*PrimaryIPsClient method*), 58
- `change_dns_ptr()` (*ServersClient method*), 64
- `change_ip_range()` (*BoundNetwork method*), 52
- `change_ip_range()` (*NetworksClient method*), 49
- `change_protection()` (*BoundFloatingIP method*), 26
- `change_protection()` (*BoundImage method*), 31
- `change_protection()` (*BoundLoadBalancer method*), 42
- `change_protection()` (*BoundNetwork method*), 52
- `change_protection()` (*BoundPrimaryIP method*), 60
- `change_protection()` (*BoundServer method*), 71
- `change_protection()` (*BoundVolume method*), 84
- `change_protection()` (*FloatingIPsClient method*), 23
- `change_protection()` (*ImagesClient method*), 28
- `change_protection()` (*LoadBalancersClient method*), 37
- `change_protection()` (*NetworksClient method*), 49
- `change_protection()` (*PrimaryIPsClient method*), 58
- `change_protection()` (*ServersClient method*), 64
- `change_protection()` (*VolumesClient method*), 81
- `change_type()` (*BoundLoadBalancer method*), 42
- `change_type()` (*BoundServer method*), 72
- `change_type()` (*LoadBalancersClient method*), 37
- `change_type()` (*ServersClient method*), 64
- `Client` (*class in hcloud*), 7
- `create()` (*CertificatesClient method*), 11
- `create()` (*FirewallsClient method*), 17
- `create()` (*FloatingIPsClient method*), 23
- `create()` (*LoadBalancersClient method*), 37
- `create()` (*NetworksClient method*), 49
- `create()` (*PlacementGroupsClient method*), 55
- `create()` (*PrimaryIPsClient method*), 58
- `create()` (*ServersClient method*), 65
- `create()` (*SSHKeysClient method*), 78
- `create()` (*VolumesClient method*), 81
- `create_image()` (*BoundServer method*), 72
- `create_image()` (*ServersClient method*), 66
- `create_managed()` (*CertificatesClient method*), 11
- `CreateFirewallResponse` (*class in hcloud.firewalls.domain*), 22
- `CreateFloatingIPResponse` (*class in hcloud.floating_ips.domain*), 28
- `CreateImageResponse` (*class in hcloud.images.domain*), 33
- `CreateNetworkResponse` (*class in hcloud.networks.domain*), 55
- `CreatePlacementGroupResponse` (*class in hcloud.placement_groups.domain*), 57
- `CreateServerResponse` (*class in hcloud.servers.domain*), 77
- `CreateVolumeResponse` (*class in hcloud.volumes.domain*), 86
- D**
- `Datacenter` (*class in hcloud.datacenters.domain*), 16
- `datacenters` (*Client attribute*), 7
- `DatacentersClient` (*class in hcloud.datacenters.client*), 15
- `DatacenterServerTypes` (*class in hcloud.datacenters.domain*), 16
- `delete()` (*BoundCertificate method*), 14
- `delete()` (*BoundFirewall method*), 20
- `delete()` (*BoundFloatingIP method*), 26
- `delete()` (*BoundImage method*), 31
- `delete()` (*BoundLoadBalancer method*), 42
- `delete()` (*BoundNetwork method*), 52
- `delete()` (*BoundPlacementGroup method*), 56
- `delete()` (*BoundPrimaryIP method*), 60
- `delete()` (*BoundServer method*), 72
- `delete()` (*BoundSSHKey method*), 80
- `delete()` (*BoundVolume method*), 84
- `delete()` (*CertificatesClient method*), 12
- `delete()` (*FirewallsClient method*), 17
- `delete()` (*FloatingIPsClient method*), 23
- `delete()` (*ImagesClient method*), 28
- `delete()` (*LoadBalancersClient method*), 38
- `delete()` (*NetworksClient method*), 50
- `delete()` (*PlacementGroupsClient method*), 55
- `delete()` (*PrimaryIPsClient method*), 58
- `delete()` (*ServersClient method*), 66
- `delete()` (*SSHKeysClient method*), 78
- `delete()` (*VolumesClient method*), 81
- `delete_route()` (*BoundNetwork method*), 53
- `delete_route()` (*NetworksClient method*), 50
- `delete_service()` (*BoundLoadBalancer method*), 43
- `delete_service()` (*LoadBalancersClient method*), 38
- `delete_subnet()` (*BoundNetwork method*), 53
- `delete_subnet()` (*NetworksClient method*), 50
- `deprecated` (*Iso property*), 34
- `DeprecationInfo` (*class in hcloud.deprecation.domain*), 87
- `detach()` (*BoundVolume method*), 84
- `detach()` (*VolumesClient method*), 82
- `detach_from_network()` (*BoundLoadBalancer method*), 43
- `detach_from_network()` (*BoundServer method*), 72
- `detach_from_network()` (*LoadBalancersClient method*), 38
- `detach_from_network()` (*ServersClient method*), 66
- `detach_iso()` (*BoundServer method*), 72
- `detach_iso()` (*ServersClient method*), 66
- `DIRECTION_IN` (*FirewallRule attribute*), 21

DIRECTION_OUT (*FirewallRule* attribute), 21
 disable_backup() (*BoundServer* method), 72
 disable_backup() (*ServersClient* method), 66
 disable_public_interface() (*BoundLoadBalancer*
 method), 43
 disable_public_interface() (*LoadBalancersClient*
 method), 38
 disable_rescue() (*BoundServer* method), 73
 disable_rescue() (*ServersClient* method), 66

E

enable_backup() (*BoundServer* method), 73
 enable_backup() (*ServersClient* method), 67
 enable_public_interface() (*BoundLoadBalancer*
 method), 43
 enable_public_interface() (*LoadBalancersClient*
 method), 39
 enable_rescue() (*BoundServer* method), 73
 enable_rescue() (*ServersClient* method), 67
 EnableRescueResponse (class in
 hcloud.servers.domain), 78

F

Firewall (class in *hcloud.firewalls.domain*), 21
 FirewallResource (class in *hcloud.firewalls.domain*),
 22
 FirewallRule (class in *hcloud.firewalls.domain*), 21
 firewalls (*Client* attribute), 7
 FirewallsClient (class in *hcloud.firewalls.client*), 17
 floating_ips (*Client* attribute), 7
 FloatingIP (class in *hcloud.floating_ips.domain*), 27
 FloatingIPsClient (class in
 hcloud.floating_ips.client), 22

G

get_actions() (*BoundCertificate* method), 14
 get_actions() (*BoundFirewall* method), 20
 get_actions() (*BoundFloatingIP* method), 26
 get_actions() (*BoundImage* method), 31
 get_actions() (*BoundLoadBalancer* method), 43
 get_actions() (*BoundNetwork* method), 53
 get_actions() (*BoundServer* method), 73
 get_actions() (*BoundVolume* method), 84
 get_actions() (*CertificatesClient* method), 12
 get_actions() (*FirewallsClient* method), 17
 get_actions() (*FloatingIPsClient* method), 24
 get_actions() (*ImagesClient* method), 28
 get_actions() (*LoadBalancersClient* method), 39
 get_actions() (*NetworksClient* method), 50
 get_actions() (*ServersClient* method), 67
 get_actions() (*VolumesClient* method), 82
 get_actions_list() (*BoundCertificate* method), 14
 get_actions_list() (*BoundFirewall* method), 20
 get_actions_list() (*BoundFloatingIP* method), 26

get_actions_list() (*BoundImage* method), 31
 get_actions_list() (*BoundLoadBalancer* method),
 43
 get_actions_list() (*BoundNetwork* method), 53
 get_actions_list() (*BoundServer* method), 73
 get_actions_list() (*BoundVolume* method), 84
 get_actions_list() (*CertificatesClient* method), 12
 get_actions_list() (*FirewallsClient* method), 18
 get_actions_list() (*FloatingIPsClient* method), 24
 get_actions_list() (*ImagesClient* method), 28
 get_actions_list() (*LoadBalancersClient* method),
 39
 get_actions_list() (*NetworksClient* method), 50
 get_actions_list() (*ServersClient* method), 67
 get_actions_list() (*VolumesClient* method), 82
 get_all() (*ActionsClient* method), 10
 get_all() (*CertificatesClient* method), 12
 get_all() (*DatacentersClient* method), 15
 get_all() (*FirewallsClient* method), 18
 get_all() (*FloatingIPsClient* method), 24
 get_all() (*ImagesClient* method), 29
 get_all() (*IsosClient* method), 33
 get_all() (*LoadBalancersClient* method), 39
 get_all() (*LoadBalancerTypesClient* method), 35
 get_all() (*LocationsClient* method), 47
 get_all() (*NetworksClient* method), 51
 get_all() (*PlacementGroupsClient* method), 55
 get_all() (*PrimaryIPsClient* method), 59
 get_all() (*ResourceActionsClient* method), 9
 get_all() (*ServersClient* method), 68
 get_all() (*ServerTypesClient* method), 62
 get_all() (*SSHKeysClient* method), 78
 get_all() (*VolumesClient* method), 82
 get_by_fingerprint() (*SSHKeysClient* method), 79
 get_by_id() (*ActionsClient* method), 10
 get_by_id() (*CertificatesClient* method), 13
 get_by_id() (*DatacentersClient* method), 15
 get_by_id() (*FirewallsClient* method), 18
 get_by_id() (*FloatingIPsClient* method), 25
 get_by_id() (*ImagesClient* method), 29
 get_by_id() (*IsosClient* method), 33
 get_by_id() (*LoadBalancersClient* method), 40
 get_by_id() (*LoadBalancerTypesClient* method), 35
 get_by_id() (*LocationsClient* method), 47
 get_by_id() (*NetworksClient* method), 51
 get_by_id() (*PlacementGroupsClient* method), 56
 get_by_id() (*PrimaryIPsClient* method), 59
 get_by_id() (*ResourceActionsClient* method), 9
 get_by_id() (*ServersClient* method), 68
 get_by_id() (*ServerTypesClient* method), 62
 get_by_id() (*SSHKeysClient* method), 79
 get_by_id() (*VolumesClient* method), 83
 get_by_name() (*CertificatesClient* method), 13
 get_by_name() (*DatacentersClient* method), 15

[get_by_name\(\)](#) (*FirewallsClient* method), 18
[get_by_name\(\)](#) (*FloatingIPsClient* method), 25
[get_by_name\(\)](#) (*ImagesClient* method), 29
[get_by_name\(\)](#) (*IsosClient* method), 33
[get_by_name\(\)](#) (*LoadBalancersClient* method), 40
[get_by_name\(\)](#) (*LoadBalancerTypesClient* method), 35
[get_by_name\(\)](#) (*LocationsClient* method), 47
[get_by_name\(\)](#) (*NetworksClient* method), 51
[get_by_name\(\)](#) (*PlacementGroupsClient* method), 56
[get_by_name\(\)](#) (*PrimaryIPsClient* method), 59
[get_by_name\(\)](#) (*ServersClient* method), 68
[get_by_name\(\)](#) (*ServerTypesClient* method), 62
[get_by_name\(\)](#) (*SSHKeysClient* method), 79
[get_by_name\(\)](#) (*VolumesClient* method), 83
[get_by_name_and_architecture\(\)](#) (*ImagesClient* method), 30
[get_list\(\)](#) (*ActionsClient* method), 10
[get_list\(\)](#) (*CertificatesClient* method), 13
[get_list\(\)](#) (*DatacentersClient* method), 16
[get_list\(\)](#) (*FirewallsClient* method), 18
[get_list\(\)](#) (*FloatingIPsClient* method), 25
[get_list\(\)](#) (*ImagesClient* method), 30
[get_list\(\)](#) (*IsosClient* method), 34
[get_list\(\)](#) (*LoadBalancersClient* method), 40
[get_list\(\)](#) (*LoadBalancerTypesClient* method), 35
[get_list\(\)](#) (*LocationsClient* method), 48
[get_list\(\)](#) (*NetworksClient* method), 51
[get_list\(\)](#) (*PlacementGroupsClient* method), 56
[get_list\(\)](#) (*PrimaryIPsClient* method), 59
[get_list\(\)](#) (*ResourceActionsClient* method), 9
[get_list\(\)](#) (*ServersClient* method), 68
[get_list\(\)](#) (*ServerTypesClient* method), 62
[get_list\(\)](#) (*SSHKeysClient* method), 79
[get_list\(\)](#) (*VolumesClient* method), 83
[get_metrics\(\)](#) (*BoundLoadBalancer* method), 44
[get_metrics\(\)](#) (*BoundServer* method), 74
[get_metrics\(\)](#) (*LoadBalancersClient* method), 40
[get_metrics\(\)](#) (*ServersClient* method), 69

H

[HCloudException](#) (class in *hcloud*), 86

I

[Image](#) (class in *hcloud.images.domain*), 32
[images](#) (Client attribute), 7
[ImagesClient](#) (class in *hcloud.images.client*), 28
[IPv4Address](#) (class in *hcloud.servers.domain*), 77
[IPv6Network](#) (class in *hcloud.servers.domain*), 77
[Iso](#) (class in *hcloud.isos.domain*), 34
[isos](#) (Client attribute), 7
[IsosClient](#) (class in *hcloud.isos.client*), 33

L

[LabelValidator](#) (class in *hcloud.helpers.labels*), 86

[load_balancer_types](#) (Client attribute), 8
[load_balancers](#) (Client attribute), 8
[LoadBalancer](#) (class in *hcloud.load_balancers.domain*), 44
[LoadBalancerAlgorithm](#) (class in *hcloud.load_balancers.domain*), 47
[LoadBalancerHealthCheckHttp](#) (class in *hcloud.load_balancers.domain*), 46
[LoadBalancerHealthCheck](#) (class in *hcloud.load_balancers.domain*), 46
[LoadBalancersClient](#) (class in *hcloud.load_balancers.client*), 36
[LoadBalancerService](#) (class in *hcloud.load_balancers.domain*), 45
[LoadBalancerServiceHttp](#) (class in *hcloud.load_balancers.domain*), 45
[LoadBalancerTarget](#) (class in *hcloud.load_balancers.domain*), 46
[LoadBalancerTargetHealthStatus](#) (class in *hcloud.load_balancers.domain*), 47
[LoadBalancerTargetIP](#) (class in *hcloud.load_balancers.domain*), 47
[LoadBalancerTargetLabelSelector](#) (class in *hcloud.load_balancers.domain*), 47
[LoadBalancerType](#) (class in *hcloud.load_balancer_types.domain*), 35
[LoadBalancerTypesClient](#) (class in *hcloud.load_balancer_types.client*), 35
[Location](#) (class in *hcloud.locations.domain*), 48
[locations](#) (Client attribute), 8
[LocationsClient](#) (class in *hcloud.locations.client*), 47

M

[model](#) (*BoundAction* attribute), 10
[model](#) (*BoundCertificate* attribute), 14
[model](#) (*BoundDatacenter* attribute), 16
[model](#) (*BoundFirewall* attribute), 20
[model](#) (*BoundFloatingIP* attribute), 27
[model](#) (*BoundImage* attribute), 32
[model](#) (*BoundIso* attribute), 34
[model](#) (*BoundLoadBalancer* attribute), 44
[model](#) (*BoundLocation* attribute), 48
[model](#) (*BoundNetwork* attribute), 53
[model](#) (*BoundPlacementGroup* attribute), 57
[model](#) (*BoundPrimaryIP* attribute), 61
[model](#) (*BoundServer* attribute), 74
[model](#) (*BoundServerType* attribute), 62
[model](#) (*BoundSSHKey* attribute), 80
[model](#) (*BoundVolume* attribute), 85

N

[Network](#) (class in *hcloud.networks.domain*), 54
[NetworkRoute](#) (class in *hcloud.networks.domain*), 55
[networks](#) (Client attribute), 8

NetworksClient (class in *hcloud.networks.client*), 48
 NetworkSubnet (class in *hcloud.networks.domain*), 54

P

placement_groups (Client attribute), 8
 PlacementGroup (class in *hcloud.placement_groups.domain*), 57
 PlacementGroupsClient (class in *hcloud.placement_groups.client*), 55
 power_off() (BoundServer method), 74
 power_off() (ServersClient method), 69
 power_on() (BoundServer method), 74
 power_on() (ServersClient method), 69
 primary_ips (Client attribute), 8
 PrimaryIP (class in *hcloud.primary_ips.domain*), 61
 PrimaryIPsClient (class in *hcloud.primary_ips.client*), 57
 PROTOCOL_ESP (FirewallRule attribute), 21
 PROTOCOL_GRE (FirewallRule attribute), 21
 PROTOCOL_ICMP (FirewallRule attribute), 21
 PROTOCOL_TCP (FirewallRule attribute), 22
 PROTOCOL_UDP (FirewallRule attribute), 22
 PublicNetwork (class in *hcloud.servers.domain*), 76

R

reboot() (BoundServer method), 74
 reboot() (ServersClient method), 69
 rebuild() (BoundServer method), 74
 rebuild() (ServersClient method), 69
 remove_from_placement_group() (BoundServer method), 74
 remove_from_placement_group() (ServersClient method), 69
 remove_from_resources() (BoundFirewall method), 20
 remove_from_resources() (FirewallsClient method), 19
 remove_target() (BoundLoadBalancer method), 44
 remove_target() (LoadBalancersClient method), 41
 request() (Client method), 8
 request_console() (BoundServer method), 74
 request_console() (ServersClient method), 70
 RequestConsoleResponse (class in *hcloud.servers.domain*), 78
 reset() (BoundServer method), 75
 reset() (ServersClient method), 70
 reset_password() (BoundServer method), 75
 reset_password() (ServersClient method), 70
 ResetPasswordResponse (class in *hcloud.servers.domain*), 77
 resize() (BoundVolume method), 85
 resize() (VolumesClient method), 83
 ResourceActionsClient (class in *hcloud.actions.client*), 9

retry_issuance() (BoundCertificate method), 14
 retry_issuance() (CertificatesClient method), 13

S

Server (class in *hcloud.servers.domain*), 75
 server_types (Client attribute), 8
 ServerCreatePublicNetwork (class in *hcloud.servers.domain*), 77
 servers (Client attribute), 8
 ServersClient (class in *hcloud.servers.client*), 63
 ServerType (class in *hcloud.server_types.domain*), 62
 ServerTypesClient (class in *hcloud.server_types.client*), 62
 set_rules() (BoundFirewall method), 20
 set_rules() (FirewallsClient method), 19
 shutdown() (BoundServer method), 75
 shutdown() (ServersClient method), 70
 ssh_keys (Client attribute), 9
 SSHKey (class in *hcloud.ssh_keys.domain*), 80
 SSHKeysClient (class in *hcloud.ssh_keys.client*), 78
 STATUS_AVAILABLE (Volume attribute), 86
 STATUS_CREATING (Volume attribute), 86
 STATUS_DELETING (Server attribute), 76
 STATUS_ERROR (Action attribute), 11
 STATUS_INIT (Server attribute), 76
 STATUS_MIGRATING (Server attribute), 76
 STATUS_OFF (Server attribute), 76
 STATUS_REBUILDING (Server attribute), 76
 STATUS_RUNNING (Action attribute), 11
 STATUS_RUNNING (Server attribute), 76
 STATUS_STARTING (Server attribute), 76
 STATUS_STOPPING (Server attribute), 76
 STATUS_SUCCESS (Action attribute), 11
 STATUS_UNKNOWN (Server attribute), 76

T

to_payload() (FirewallResource method), 22
 to_payload() (FirewallRule method), 22
 to_payload() (LoadBalancerService method), 45
 to_payload() (LoadBalancerTarget method), 47
 TYPE_CLOUD (NetworkSubnet attribute), 54
 TYPE_LABEL_SELECTOR (FirewallResource attribute), 22
 TYPE_SERVER (FirewallResource attribute), 22
 TYPE_SERVER (NetworkSubnet attribute), 54
 TYPE_VSWITCH (NetworkSubnet attribute), 55

U

unassign() (BoundFloatingIP method), 27
 unassign() (BoundPrimaryIP method), 61
 unassign() (FloatingIPsClient method), 25
 unassign() (PrimaryIPsClient method), 59
 update() (BoundCertificate method), 14
 update() (BoundFirewall method), 20
 update() (BoundFloatingIP method), 27

`update()` (*BoundImage method*), 32
`update()` (*BoundLoadBalancer method*), 44
`update()` (*BoundNetwork method*), 53
`update()` (*BoundPlacementGroup method*), 57
`update()` (*BoundPrimaryIP method*), 61
`update()` (*BoundServer method*), 75
`update()` (*BoundSSHKey method*), 80
`update()` (*BoundVolume method*), 85
`update()` (*CertificatesClient method*), 13
`update()` (*FirewallsClient method*), 19
`update()` (*FloatingIPsClient method*), 25
`update()` (*ImagesClient method*), 30
`update()` (*LoadBalancersClient method*), 41
`update()` (*NetworksClient method*), 52
`update()` (*PlacementGroupsClient method*), 56
`update()` (*PrimaryIPsClient method*), 60
`update()` (*ServersClient method*), 70
`update()` (*SSHKeysClient method*), 79
`update()` (*VolumesClient method*), 83
`update_service()` (*BoundLoadBalancer method*), 44
`update_service()` (*LoadBalancersClient method*), 41

V

`validate()` (*LabelValidator static method*), 86
`validate_verbose()` (*LabelValidator static method*),
87
`Volume` (*class in hcloud.volumes.domain*), 85
`volumes` (*Client attribute*), 9
`VolumesClient` (*class in hcloud.volumes.client*), 81

W

`wait_until_finished()` (*BoundAction method*), 10